

AOC Active Optical Cable - DisplayPort 8K@60Hz - 32.4Gbps V1.4 Cable - CMP Plenum Rated

DP-200-xxPL - Specifications

Description

This active optical DisplayPort cable is plenum rated and consists of a DisplayPort male connector on both ends. The cable has a built in signal booster chipset which supports DisplayPort 1.4 and provides a wide range of features in a compact, lightweight form-factor. These cables are fully HDCP 1.4 / 2.2 compliant and supports signals with data rates up to 32.4 Gbps (HBR3). It is typically used to connect a DisplayPort source such as a PC or laptop to a monitor and supports full 8K Ultra HD resolution at60Hz (4:4:4) up to 100 meters.

This active optical DP cable is directional. Each end of the cable is marking "Source" and "Display" to indicate the direction of the signal flow. Always test the cable to be sure that the signal flow is correct and for device compatibility before permanently installing in a wall or ceiling.

Physical Characteristics

Color Black

Connector Plating Gold

Shell Material Zinc-Alloy

Cable Specs Fiber Optic 50/125um multimode / Copper

Cable Diameter 4.8mm

Shielding 75% Braid + 100% Aluminum-Mylar Foil

Jacket Fire Rating CMP

Jacket Material PVC

Strain Relief Molded PVC

Performance

Resolution Ultra HD 8K @ 60Hz

Chroma Sampling 4:4:4

Bandwidth 32.4Gbps, 8.1 Gbps per channel

Supported Distance 100m

Support HBR3, HDCP

HDCP Compliant Yes, 1.4 / 2.2

DisplayPort Version v1.4





AOC Active Optical Cable - DisplayPort 8K@60Hz - 32.4Gbps V1.4 Cable - CMP Plenum Rated DD 200 vvDl Specifications

DP-200-xxPL - Specifications

Approvals

c(UL)us Yes, Cable

CE Yes

FCC Yes

Environmental

RoHS Yes

Reach Yes

Conflict Minerals Yes

Packaging Information

Package Quantity

Warranty Information

Warranty Limited Lifetime

Cable Weights

15ft 25ft 35ft 50ft 75ft 100ft 150ft

0.50 lbs (0.22 kg) 0.70 lbs (0.32 kg) 0.80 lbs (0.36 kg) 1.05 lbs (0.47 kg) 1.50 lbs (0.68 kg) 2.65 lbs (1.20 kg) 3.50 lbs (1.58 kg)