



DisplayPort Male to DisplayPort Male Cable - 4Kx2K 60Hz FT4 26AWG

DP-DPC-xx- Specifications

Description

This cable consists of a DisplayPort male on one end and a DisplayPort male on the other end. It is typically used to connect a DisplayPort source to a DisplayPort monitor.

Physical Characteristics

| | |
|--------------------|--------------------------|
| Color | Black |
| Connector Plating | Gold |
| Cable Diameter | 7.3 mm |
| Wire Gauge | 26AWG |
| Jacket Material | PVC - Polyvinyl Chloride |
| Jacket Rating | CL3, FT4 Riser Rated |
| Cable Shielding | Yes |
| Strain Relief | Molded PVC |
| Temperature Rating | 80 deg C |

Connector(s)

| | |
|-------------|------------------|
| Connector A | DisplayPort Male |
| Connector B | DisplayPort Male |

Performance

| | |
|--------------------|-------------------------------|
| Maximum Bandwidth | 10.8 Gbps (2.7Gbps * 4 lanes) |
| Maximum Resolution | 4K x 2K (3840 x 2160) |
| Maximum Frequency | 60Hz |
| 3D Support | Yes |
| DP Version | v1.1 |

Approvals

| | |
|---------|-----|
| c(UL)us | Yes |
|---------|-----|

Environmental

| | |
|-------------------|-----|
| RoHS | Yes |
| Reach | Yes |
| Conflict Minerals | Yes |

Packaging Information

| | |
|------------------|---|
| Package Quantity | 1 |
|------------------|---|

Warranty Information

| | |
|----------|------------------|
| Warranty | Limited Lifetime |
|----------|------------------|

Cable Weights

| | |
|----------|----------|
| 15ft | 25ft |
| 0.65 lbs | 1.30 lbs |

