



DP1.2 Male to HDMI Male Cable, 4K@60Hz, HDR, CEC, HDCP2.2, 32AWG - Black

DP-HD100-xx - Specifications

Description

This cable has a DisplayPort male on one end and a HDMI male on the other. It is used to connect a DP source to a HDMI display. It cannot be used to connect a HDMI source to a DisplayPort monitor.

Features:

- Supports DP1.2 Alt mode with 21.6Gbps all lanes, per lane 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR)
- Supports HDMI max 4K/60Hz, 8 bit with max 18Gbps
- Supports RGB 4:4:4, YCbCr 4:4:4 ,4:2:2 ,4:2:0
- Supports 8bit/10bit/12bit deep color
- Supports HDR
- Supports HDCP2.2 & 1.4
- Supports CEC

Physical Characteristics

Color	Black
Connector Plating	Nickel
Dimensions	DP connector: 28L x 19.8W x 9.8Hmm HDMI connector: 43.2L x 20.8W x 11Hmm
Wire Gauge	32 AWG
Cable Outer Diameter	4.9mm
Operating Temperature	0 °C to +45°C
& Humidity	10% to 90 % RH (no condensation)
Storage Temperature	0°C to +70°C
& Humidity	10% to 90 % RH (no condensation)

Certifications

FCC, CE	Approved Cable
---------	----------------





DP1.2 Male to HDMI Male Cable, 4K@60Hz, HDR, CEC, HDCP2.2, 32AWG - Black

DP-HD100-xx - Specifications

Connectors

Connector A	HDMI Male
Connector B	DisplayPort Male

Performance

DisplayPort	DP Version 1.2 DP1.2 Alt mode with 21.6Gbps all lanes per lane 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR)
HDMI	Up to HDMI max 4K/60Hz, 8bit, 18Gbps Supports RGB 4:4:4, YCbCr 4:4:4 ,4:2:2 ,4:2:0 Supports 8bit/10bit/12bit deep color Supports HDR Supports HDCP2.2 & 1.4 Supports CEC

Environmental

RoHS	Yes
Reach	Yes
Conflict Minerals	Yes

Packaging Information

Packaging Quantity	1
Product Weight	3ft - 0.08lbs 6ft - 0.15lbs

Warranty Information

Warranty	Limited Lifetime
----------	------------------