

Premium Phantom Cables DS3 734A Simplex BNC Male to BNC Male

DS3-100-xx - Specifications

Description

This DS3 (T3) 734A simplex cable has a BNC male on both ends. This 75 ohm telephony coaxial cable is typically used for the interconnection of

transmission equipment.

• Superior structural return loss and attenuation performance

• Silver plated copper cable for better attenuation performance

• Heavy duty connectors allow for optimum durability and connectivity

Physical Characteristics

Color Grey

Connector Plating Nickel

Cable Type Belden 734A1 Single Coax 20 AWG Solid

Cable Jacket Material Polyvinyl Chloride (PVC)

Operating Temperature -40C to $+75^{\circ}C$

Fire Rating FT4, UL1666

Connectors

Connector A BNC Male

Connector B BNC Male

Performance

Impedance	75 ohm	Cable Weights					
Packaging Information		3ft	6ft	10ft	15ft	25ft	35ft
Package Quantity	1 Cable	0.35lbs	0.70lbs	1.07lbs	01.77lbs	2.84lbs	3.91lbs
Warranty Information		50ft	75ft	100ft	150ft	200ft	
Warranty	Limited Lifetime	5.68lbs	8.52lbs	11.36lbs	17.04lbs	22.72lbs	

~ 11 14/ 11/

