



Premium Phantom Cables DS3 734A Simplex BNC Male to LCC Male

DS3-110-xx - Specifications

Description

This DS3 (T3) 734A simplex cable has a BNC male on one end, and a LCC male on the other. This 75 ohm telephony coaxial cable is typically used for the interconnection of transmission equipment.

- Superior structural return loss and attenuation performance
- Silver plated copper cable for better attenuation performance
- Heavy duty connectors allow for optimum durability and connectivity

Physical Characteristics

Color	Grey
Connector Plating	Nickel
Cable Type	Belden 734A1 Single Coax 20 AWG Solid
Cable Jacket Material	Polyvinyl Chloride (PVC)
Operating Temperature	-40C to +75°C
Fire Rating	FT4, UL1666

Connectors

Connector A	BNC Male
Connector B	LCC Male

Performance

Impedance	75 ohm
-----------	--------

Packaging Information

Package Quantity	1 Cable
------------------	---------

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

3ft	6ft	10ft	15ft	25ft	35ft
0.35lbs	0.70lbs	1.07lbs	01.77lbs	2.84lbs	3.91lbs
50ft	75ft	100ft	150ft	200ft	
5.68lbs	8.52lbs	11.36lbs	17.04lbs	22.72lbs	

