



Description

This DS3 (T3) 735A Duplex cable has two BNC Male on one end, and two LCC Male on the other. This 75 ohm telephony coaxial cable is typically used for the interconnection of transmission equipment.

- Superior structural return loss and attenuation performance
- Silver plated copper cable for better attenuation performance
- Heavy duty connectors allow for optimum durability and connectivity

Physical Characteristics

Length	3ft / 6ft / 10ft / 15ft / 25ft / 35ft / 50ft / 75ft/ 100ft / 150ft / 200ft
	*Custom Lengths Available
Color	Grey
Contact Plating	Nickel
Cable Type	Belden 735A2 Dual Coax 26 AWG Solid
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4, UL1666
Operating Temperature	-40C to +75C

Connectors

Connector A	2 - BNC Male
Connector B	2 - LCC Male

Performance

Impedance	75 ohm
-----------	--------

Packaging Information

Package Quantity	1 Cable
------------------	---------

Cable Weights

3ft	6ft	10ft	15ft	25ft	35ft	50ft	75ft	100ft	150ft	200ft
0.35lbs	0.70lbs	1.07lbs	01.77lbs	2.84lbs	3.91lbs	5.68lbs	8.52lbs	11.36lbs	17.04lbs	22.72lbs

