

Premium Phantom Cables DS3 735A Duplex BNC Male to DIN 1.0/2.3 Male

DS3-415-xx- Specifications

Description

This DS3 (T3) 735A Duplex cable has two BNC Male on one end, and two DIN 1.0/2.3 Male on the other. This 75 ohm telephony coaxial cable is typically used for the interconnection of transmission equipment.

- Superior structural return loss and attenuation performance
- Silver plated copper cable for better attenuation performance
- Heavy duty connectors allow for optimum durability and connectivity

Physical Characteristics

Length 3ft / 6ft / 10ft / 15ft / 25ft / 35ft / 50ft / 75ft/ 100ft / 150ft / 200ft

*Custom Lengths Available

Color Grey

Contact Plating Nickel

Cable Type Belden 735A2 Dual Coax 26 AWG Solid

Jacket Material PVC - Polyvinyl Chloride

Fire Rating FT4, UL1666

Operating Temperature -40C to +75C

Connectors

Connector A 2 - BNC Male

Connector B 2 - DIN 1.0/2.3 Male

Performance

Impedance 75 ohm

Packaging Information

Package Quantity 1 Cable

Cable Weights

3ft	6ft	10ft	15ft	25ft	35ft	50ft	75ft	100ft	150ft	200ft
0.35lbs	0.70lbs	1.07lbs	01.77lbs	2.84lbs	3.91lbs	5.68lbs	8.52lbs	11.36lbs	17.04lbs	22.72lbs

