



Description

This DS3 (T3) 735A Duplex cable has two BNC Female on one end, and two DIN 1.0/2.3 Male on the other. This 75 ohm telephony coaxial cable is typically used for the interconnection of transmission equipment.

- Superior structural return loss and attenuation performance
- Silver plated copper cable for better attenuation performance
- Heavy duty connectors allow for optimum durability and connectivity

Physical Characteristics

|                       |  |
|-----------------------|--|
| Length                | 3ft / 6ft / 10ft / 15ft / 25ft / 35ft / 50ft / 75ft/ 100ft / 150ft / 200ft |
|                       | *Custom Lengths Available  |
| Color                 | Grey   |
| Contact Plating       | Nickel   |
| Cable Type            | Belden 735A2 Dual Coax 26 AWG Solid  |
| Jacket Material       | PVC - Polyvinyl Chloride   |
| Fire Rating           | FT4, UL1666  |
| Operating Temperature | -40C to +75C   |

Connectors

|             |                      |
|-------------|----------------------|
| Connector A | 2 - BNC Female       |
| Connector B | 2 - DIN 1.0/2.3 Male |

Performance

|           |        |
|-----------|--------|
| Impedance | 75 ohm |
|-----------|--------|

Packaging Information

|                  |         |
|------------------|---------|
| Package Quantity | 1 Cable |
|------------------|---------|

Cable Weights

| 3ft     | 6ft     | 10ft    | 15ft     | 25ft    | 35ft    | 50ft    | 75ft    | 100ft    | 150ft    | 200ft    |
|---------|---------|---------|----------|---------|---------|---------|---------|----------|----------|----------|
| 0.35lbs | 0.70lbs | 1.07lbs | 01.77lbs | 2.84lbs | 3.91lbs | 5.68lbs | 8.52lbs | 11.36lbs | 17.04lbs | 22.72lbs |

