

LSZH/OFNR

FO-305-xx - Specifications

## **Description**

This 50 micron (OM2) fiber optic cable is made with Corning glass fiber. It has 3mm jacket and rated low smoke zero halogen (LSZH) & riser (OFNR). They are tested to provide the optimum data transmission and network stability. They are used for connections to data center, CATV, fiber test equipment, LAN, telecommunication networks, FTTx, communication rooms and fiber optic communication system.

## **Physical Characteristics**

Color	Orange
Cable Diameter	3mm
Fiber Size	50/125 micron
Fiber Type	Multimode
Glass Manufacturer	Corning Glass
Connector Ferules	Ceramic
Fiber Classification	OM2
Jacket Rating	Riser (OFNR) & Low Smoke Zero Halogen (LSZH)
Operating Temperature	-20 deg C ~ +70 deg C
<u>Connectors</u>	
Connector A	MTRJ Duplex Male
Connector B	MTRJ Duplex Male
Performance	
Insertion Loss	<0.3db @ 1300nm
Speed	1 Gbps
Interferometer Tested	100% Tested
<b>Environmental</b>	
RoHS	Yes
Conflict Minerals	Yes
Packaging Information	
Package Quantity	1
Warranty Information	
Warranty	Limited Lifetime