



# Premium Phantom Cables 5-Pin MIDI Male To Male Cable FT4

## MIDI-MM-xx - Specifications

### Description

This premium 5-pin MIDI cable has a din 5-pin male on one end and a din 5-pin male on the other. It is typically used to connect MIDI equipment such as electronic musical instruments and computers.

- Hi-flex cable is used to capture all highs & lows for optimum audio performance
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

### Physical Characteristics

Color	Black
Contact Plating	Nickel
Cable Diameter	6.8mm
Wire Gauge	24AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Bare Copper Braid, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

### Connectors

Connector A	Din 5-Pin Male
Connector B	Din 5-Pin Male

### Approvals

cUL	Yes - Cable
-----	-------------

### Environmental

RoHS	Yes
------	-----

### Warranty Information

Warranty	Limited Lifetime
----------	------------------

### Package Information

Package Quantity	1
------------------	---

### Cable Weights

<b>1.5ft</b>	<b>3ft</b>	<b>6ft</b>	<b>10ft</b>	<b>15ft</b>
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs
<b>25ft</b>	<b>35ft</b>	<b>50ft</b>	<b>75ft</b>	<b>100ft</b>
1.00 lbs	1.30 lbs	1.75 lbs	2.75 lbs	3.52 lbs

