



Neutrik DMX 5-pin Male to Solder D-Cut Receptacle

NT-NC5MD-L-1 - Specifications

Description

This connector is a 5-pin male receptacle with solder cups, nickel housing and silver contacts.

Physical Characteristics

Color	Nickel
Connector Type	XLR
Temperature Range	-30°C to +80°C
Contact Plating	2 µm Au over 2 µm Ni
Contacts	Brass
Insert	Polyamide
Locking Element	Steel Ck67
Shell	Zinc Diecast
Shell Plating	Nickel
Gender	Male

Electrical Characteristics

Capacitance between Contacts	≤ 7 pF
Contact Resistance	≤ 5 mΩ
Dielectric Strength	1,5 kVdc
Insulation Resistance	> 10 GΩ (initial)
Rated Current Per Contact	7,5 A
Rated Voltage	< 50 V

Manufacturer Information

Neutrik Part Number	NC5MD-L-1
---------------------	-----------

Packaging Information

Package Quantity	1
Product Weight	0.02 lbs [0.01 kg]





Neutrik DMX 5-pin Male to Solder D-Cut Receptacle

NT-NC5MD-L-1 - Specifications

Mechanical Characteristics

Insertion Force	≤ 20 N
Withdrawal Force	≤ 20 N
Lifetime	> 1000 mating cycles
Wire size	Max. 1.0 mm ² Max. 18 AWG
Wiring	Solder contacts
Locking Device	Latch Lock
Chassis Shape	D

Approvals

UL	Yes
----	-----

Environmental

Flammability	UL 94 HB
Standard Compliance	IEC 61076-2-103
Protection Class	IP 40
Solderability	Complies with IEC 68-2-20

