



Neutrik 90 Degree 1/4 inch TS Male Slim Plug - Black with Gold Pins

NT-NP2RX-B - Specifications

Description

This heavy duty professional plug is typically used for guitar applications, audio cables, snakes, speakers, amplifiers and mixing decks.

Physical Characteristics

| | |
|-------------------|-----------------------|
| Color | Black |
| Housing | Metal |
| Temperature Range | -20°C to +65°C |
| Bushing | Polyacetal (POM) + PU |
| Contact Plating | 0.2 µm Au |
| Contacts | Brass |
| Insert | Polyamide |
| Shell | Zinc Diecast |
| Shell Plating | Black Chromium |
| Strain Relief | Polyacetal (POM) |
| Gender | Male |

Electrical Characteristics

| | |
|---------------------------|----------------------------------|
| Contact Resistance | Depending on Mating Connector mΩ |
| Dielectric Strength | 1 kVdc |
| Insulation Resistance | > 2 GΩ (initial) |
| Rated Current Per Contact | Depends on Mating Connector A |
| Rated Voltage | < 50 V |





Neutrik 90 Degree 1/4 inch TS Male Slim Plug - Black with Gold Pins

NT-NP2RX-B - Specifications

Mechanical Characteristics

| | |
|------------|----------------------|
| Cable O.D. | 4 - 7 mm |
| Lifetime | > 1000 Mating Cycles |
| Wire size | 1 mm ² |
| | 18 AWG |
| Wiring | Solder contacts |

Environmental

| | |
|---------------------|---------------------------|
| Standard Compliance | IEC 60603-11 / EIA RS-453 |
| Solderability | Complies with IEC 68-2-20 |

Manufacturer Information

| | |
|---------------------|---------|
| Neutrik Part Number | NP2RX-B |
|---------------------|---------|

Packaging Information

| | |
|------------------|--------------------|
| Package Quantity | 1 |
| Product Weight | 0.02 lbs [0.01 kg] |

