



Neutrik 4.4mm Bantam Plug (Solder + Crimp) - Black

NT-NP3TT-P-B - Specifications

Description

This 4.4mm plug is designed for pro audio applications and is ideal for the usage of Bantam patch panels. It has a robust ergonomic design that is long-lasting and dependable.

Physical Characteristics

| | |
|----------------------------|----------------------------------|
| Color | Black |
| Housing | Plastic |
| Temperature Range | -20°C to +65°C |
| Contact Plating | 2 µm Ni |
| Contacts | Bronze |
| Shell | Polyamide |
| Insulation | Polyamide |
| Gender | Male |
| Electrical Characteristics | |
| Contact Resistance | Depending on Mating Connector mΩ |
| Dielectric Strength | 1 kVdc |
| Insulation Resistance | > 2 GΩ (initial) |
| Rated Current Per Contact | Depends on Mating Connector A |
| Rated Voltage | < 50 V |





Neutrik 4.4mm Bantam Plug (Solder + Crimp) - Black

NT-NP3TT-P-B - Specifications

Mechanical Characteristics

| | |
|------------|--|
| Cable O.D. | 4 - 4.8 mm |
| Crimp Size | 5,41 Hex Crimp (Shield) acc. IEC 60803 (Die Designation D) |
| Lifetime | > 1000 mating cycles |
| Wire size | 0,25 mm ² 24 AWG |
| Wiring | Solder contacts |

Environmental

| | |
|---------------------|---------------------------|
| Standard Compliance | MIL-P-642/13 |
| Solderability | Complies with IEC 68-2-20 |

Manufacturer Information

| | |
|---------------------|-----------|
| Neutrik Part Number | NP3TT-P-B |
|---------------------|-----------|

Packaging Information

| | |
|------------------|--------------------|
| Package Quantity | 1 |
| Product Weight | 0.02 lbs [0.01 kg] |

