Description

This 24 port Cat6A 1U shielded patch panel has RJ45 female to female feed-through keystone couplers on both ends. It is meant to be mounted on a 19" rack or cabinet and provides an easy method to couple Cat6A patch cables.

Physical Characteristics

Color	Black (Powder Coat)
Material	Steel
Connector Type	CAT6A Shielded
Ports	24
Rack Space	1U
Product Dimensions	19" W x 3.5" H [48 cm W x 8.9 cm H]
Rackmountable	Yes, 19" Rack or Cabinet
Cable Management	Yes

Connectors

Front	24 - RJ45 Cat6a Female
Rear	24 - RJ45 Cat6a Female

Environmental

RoHS	Yes

Built from components:

PP-24KSS-1U

JK-C6A-FFS

Packaging Information

Package Quantity	1 - Patch Panel
	1 - Grounding Cable
	1 - Screw
	25 - Cable Ties
Product Weight	2.5 lbs [1.13 kg]

Ground Wire

1

2-1

3

4

5

2-2

SCALE 1/5

400.0±10.0mm

11.5±0.2

6.5±0.2

150.0±0.3

445.0±0.5

19 Inch(482.6±0.5mm)

464.8±0.5

16.2

14.6

18.2±0.1

31.8±0.2

43.6±0.3

Specification :

Material :
1. Support Bar : SPCC, 1.5mm thickness with Black(RAL 9005) color painted.
2. Rear Panel :
    2-1 Rear Panel : SPCC, 1.5mm thickness with Zinc-plated.
    2-2 Front Plate Edge : Black (RAL 9005) color painted after zinc-plated
          for both side.
3. Front Plate : ABS, UL 94-HB.
4. Identification :
    4-1. Paper.
    4-2. I.D. Plate : PC, UL 94V-2.
5. Ground Wire : 18 AWG Wire, with Green/Yellow striped color, length 40 cm.

SCALE 1/1

35.2±0.3

14.5±0.2

17.1±0.2

21.2±0.2

16.1±0.2

CAT.6A

6.9

PIN.1   PIN.8

11.9

PIN.8   PIN.1

Specification :

Material :
1. RJ45 Jack Housing : ABS+PC, UL 94V−0, with Black color.
2. Contact Bracket : PC, UL 94V−2, Transparent color.
3. RJ45 Jack Shield : Bronze with Nickel plated.
4. RJ45 Jack Contact :
   4−1. Material : Phosphor Bronze with Nickel plated.
   4−2. Finish : 50 micro−inch Gold plated on Plug contact area.
5. PCB : FR4, UL 94V−0.