



IEC C19 to IEC C20 Right Angle Power Cable - 12AWG

PW-125R0-xx - Specifications

Description

This power cord consists of a C20 right angle male on one end and a C19 female on the other end. It is typically used to connect a server to a PDU in a data center environment. These cables are constructed with UL mandated inner plastic frame molds to enhance terminal alignment and produce a high quality connector. The connectors premium quality ensures a snug fit with receptacles. Each assembly is 100% continuity tested and 100% HVT (High Voltage) tested and inspected before shipping.

Physical Characteristics

Colors Available	Black
Lengths Available	2ft / 3ft / 4ft / 6ft / 10ft
Number of Conductors	3 Conductor
Wire Gauge	12 AWG
Jacket	Heavy Duty SJT
Jacket Material	100% Virgin PVC - Polyvinyl Chloride
Jacket Fire Rating	VW-1, FT2
Strain Relief	Molded 100% Virgin PVC
Temperature Rating	-20 deg C to 105 deg C

Connector(s)

Connector A	IEC 60320 C19
Connector B	IEC 60320 C20 Right Angle

Performance

Power Rating	20 Amp / 250 Volt
--------------	-------------------


Approvals / Environmental

C19	c(UL)us
C20	c(UL)us
Cable	c(UL)us
ISO	ISO 9001:2015, ISO 14000
RoHS	Yes
Reach	Yes
Conflict Minerals	Yes

Warranty Information

Warranty	Limited Lifetime
----------	------------------





MARKING:

c(UL)us E241374 SJT 3/C 12AWG(3.31mm²) 105°C 300V VW-1

Tolerance

>0±0.30

>1.0±0.50

>10.0±1.0



>20.0±2.0

Angle: ±1°



IEC C19 to IEC C20 Right Angle Power Cable - 12AWG

PW-125R0-xx - Packaging Information



Black Logo

THE INDIVIDUALLY PACKED CORDS WILL
BE PACKED IN BAGS OF 10 PIECES

P/N	LENGTH(Lmm)	UPC
PW-125R0-02	610mm	675678003259
PW-125R0-03	915mm	675678003266
PW-125R0-04	1220mm	675678003273
PW-125R0-06	1830mm	675678003280
PW-125R0-10	3050mm	675678004706

