

1ft NEMA 5-15P to NEMA 5-20R Power Cable - 14AWG

PWC-112C-01 - Specifications

Description

This power cord consists of a 5-15P male on one end and a 5-20R female on the other end. It is typically used as an extension cable. These cables are constructed with UL mandated inner plastic frame molds to enhance terminal alignment and produce a high quality connector. The connectors premium quality ensures a snug fit with receptacles. Each assembly is 100% continuity tested and 100% HVT (High Voltage) tested and inspected before shipping.

Physical Characteristics

Color Length Number of Conductors Wire Gauge Jacket Jacket Material Jacket Fire Rating Strain Relief Temperature Rating	Black 1 foot [0.3m] 3 Conductor 14 AWG Heavy Duty SJT 100% Virgin PVC - Polyvinyl Chloride FT2, VW-1 Molded 100% Virgin PVC -20 deg C to 105 deg C
Connector A Connector A Connector B Performance Power Rating	NEMA 5-15P NEMA 5-15R/5-20R T-Slot 15 Amp / 125 Volt
Approvals / Environmental 5-15P 5-20R Cable ISO RoHS Reach	c(UL)us c(UL)us c(UL)us ISO 9001:2015, ISO 14000 Yes Yes
Conflict Minerals	Yes
Warranty Information	
Warranty	Limited Lifetime