



NEMA 6-20P to IEC C13 Power Cable - 14AWG

PWC-140-xx - Specifications

Description

This power cord consists of a 6-20P male on one end and a C13 female on the other end. It is typically used with bitcoin mining machines, and to connect a server or UPS to a PDU or a wall outlet. These cables are constructed with UL mandated inner plastic frame molds to enhance terminal alignment and produce a high quality connector. The connectors premium quality ensures a snug fit with receptacles. Each assembly is 100% continuity tested and 100% HVT (High Voltage) tested and inspected before shipping.

Physical Characteristics

Colors	Black
Lengths Available	2ft / 3ft / 4ft / 6ft / 10ft / 12ft / 15ft
Number of Conductors	3 Conductor
Wire Gauge	14 AWG
Jacket	Heavy Duty SJT
Jacket Material	100% Virgin PVC - Polyvinyl Chloride
Jacket Fire Rating	VW-1
Strain Relief	Molded 100% Virgin PVC
Conductor Material	100% bare copper
Temperature Rating	-20 deg C to 105 deg C

Connector(s)

Connector A	NEMA 6-20P
Connector B	IEC C13

Performance

Power Rating	15 Amp / 250 Volt
--------------	-------------------




Approvals / Product Support

6-20P	c(UL)us
C13	c(UL)us
Cable	c(UL)us
ISO	ISO 9001:2015, ISO 14000
RoHS, Reach	Yes
Conflict Minerals	Yes
Country of Origin	Vietnam

Warranty Information

Warranty	Limited Lifetime
----------	------------------





NEMA 6-20P

IEC 320 C13



CABLE MARKING:

Phantom Cables c(UL)us E345578 SJT 3/C 14AWG(2.08mm²) 105°C 300V VW-1

	P1	P2
BLACK	L	L
WHITE	N	N
GREEN	E	E


Cable Length
Unless Other Spec.
Tolerances:

0 ~200mm	±10mm
201~1000mm	±20mm
1001 ~1500mm	±25mm
1501~2100mm	±30mm
2100mm↑	±40mm

THE CABLE MARKING IS CONCAVE LETTERING MOULD


PACKING A: ≤1FT

PACKING B: >2FT




P/N	LENGTH(Lmm)	UPC
PWC-140-02	610mm	675678061747
PWC-140-03	915mm	675678061754
PWC-140-04	1219mm	675678061761
PWC-140-06	1830mm	675678061778
PWC-140-10	3048mm	675678061785
PWC-140-12	3658mm	675678061792
PWC-140-15	4572mm	675678061808

PACKING:
1PCS IN A ZIP BAG





LABEL

PACKING: 1-10FT
10PCS IN A BIG POLYBAG



LABEL A



*NOTE: All relevant materials are complied with RoHS directive .