

NEMA 5-15P to 3x NEMA 5-15R Power Splitter Cable - SJT - 14AWG

PWC-310C-xx - Specifications

Description

This power cord consists of a 5-15P male on one end and three 5-15R females on the other end. It is typically used on devices with multiple power supplies sharing one receptacle. These cables are constructed with UL mandated inner plastic frame molds to enhance terminal alignment and high quality molds. The connectors premium quality to ensure a snug fit into PDU receptacles. Each assembly is 100% continuity tested and 100% HVT (High Voltage) tested and inspected before shipping.

Physical Characteristics

<u>Filysical Characteristics</u>	
Colors	Black
Number of Conductors	3 Conductor
Wire Gauge	14AWG
Jacket	Heavy Duty SJT
Jacket Material	100% Virgin PVC - Polyvinyl Chloride
Jacket Fire Rating	VW-1
Strain Relief	Molded 100% Virgin PVC
Conductor Material	100% bare copper
Temperature Rating	-20 deg C to 105 deg C
Split Length <u>Connectors</u>	200mm [0.65ft]
Connector A	NEMA 5-15P
Connector B	NEMA 5-15R
Connector B	NEMA 5-15R
Connector B	NEMA 5-15R
Performance	
Power Rating	15 Amp / 125 Volt
Approvals/Environmental	
5-15P, 5-15R. 5-15R. 5-15R, Cable	c(UL)us
ISO	ISO 9001:2015, ISO 14000
RoHS/Reach/Conflict Minerals	Yes
Country of Origin	Vietnam
Packaging Information	
Package Quantity	1
Warranty Information	
Warranty	Limited Lifetime

NEMA 5-15P to 3x NEMA 5-15R Power Splitter Cable - SJT - 14AWG PHANTOM CABLES PWC-310C-xx - Line Drawing -200--200 17.5±0.2 43.0±0.2 -27.0±0.2-P2 -36.0±0.2 PC-108 RoHS Max 21.4 -37.6±0.2 -14.0±0.2 NEMA 5-15R 888 -27.0±0.2-Hin 15.9 0 0 17.5±0.2 43.0±0.2 -30±5 -TRANSPARENCE SOFT CABLE TIE 888 24.8±0.2 Phantom Cables 0)- EMS577 PC-13958 888 P1 Н 36.0±0.2 Ρ3 N [] PC-105 [] L 888 PC-108 888 -22.2±0.2 AAA RoHS 0 -LABEL A 0 NEMA 5-15R NEMA 5-15P -27.0±0.2-P5 17.5±0.2 43.0±0.2 -LABEL D 888 36.0±0.2 0 0 Ρ4 Hⁱ 888 PC-108 888 888 50.5±0.5 Cables -LABEL D RoHS NEMA 5-15R 888 0000 888 0 0 63.0±0.5 MARKING: Phantom Cables c(UL)us E345578 SJT 3/C 14AWG(2.08mm²) 105°C 300V VW-1 Cable Length Unless Other Spec. Tolerances: P2 Ρ3 P1 Ρ4 0~200mm BLACK +10mm WHITE ٠N GREEN E 201~1000mm ±20mm 1001 ~1500mm ±25mm P1,P2,P3,P4: cOus E345577 1501~2100mm ±30mm

THE CABLE MARKING IS CONCAVE LETTERING MOULD

±40mm

2100mm

