

## Premium Phantom Cables RG59 RCA Male to BNC Male Cable FT4

RCA-BNCPH-xx- Specifications

## Description

This premium cable consists of a RCA male connector on one end and a BNC connector on the other end. It is used to connect a professional video camera to a video display.

Constructed of low-loss, High Definition 75 ohm multi-stranded, heavy gauge cable for premium performance and maximum flexibility

FPE dielectric insulation allows for a stable velocity of propagation therefore minimizing possible timing delays

Cables nominal capacitance is an exceptional 18.6 pf/ft and has a nominal attenuation of 3.00 dB/100ft

Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid

Durable cable jacket is ultra flexible to maximize mobility

High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity

• The connector backshells are made of a durable, zinc plated metal alloy

Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

## **Physical Characteristics**

Color Black

Connector Plating Gold

22AWG Stranded Cable Diameter

RG59 Cable Type

**Jacket Material** PVC - Polyvinyl Chloride

Fire Rating FT4 (Riser CMR)

Cable Shielding 95% Bare Copper Braid, 100% Aluminum Mylar Foil

Insulation Foam Polyethylene

Strain Relief Metal Shell

**Performance** 1 - Cable Package Quantity

75 Ohm **Impedance** 

Velocity of Propagation 78% Limited Lifetime Warranty

Capacitance 18.6 PF/FT

Connector(s)

Connector A 1 - RCA Male

Connector B 1 - BNC Male

**Approvals** 

c(UL)us Yes - Cable **Packaging Information** 

**Warranty Information** 

**Cable Weights** 

35ft 3ft 6ft 10ft 15ft 25ft 0.40 lbs 0.55 lbs 0.75 lbs 1.00 lbs 1.50 lbs 2.00 lbs

50ft 75ft 100ft

2.75 lbs 4.00 lbs 5.25 lbs

