



Premium Phantom Cables Subwoofer RCA Male to Male Cable FT4

SUB-RCA1-xx - Specifications

Description

This premium double shielded audio cable has a RCA male on one end and a RCA male on the other. It is typically used to connect to a subwoofer to a receiver.

- Constructed of double shielded, true 75 ohm coax cable for ultra crisp sounding audio
- FPE dielectric insulation allows for a stable velocity of propagation therefore minimizing possible timing delays
- Cables nominal capacitance is an exceptional 18.6 pf/ft and has a nominal attenuation of 3.00 dB/100ft
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- The connector backshells are made of a durable, zinc plated metal alloy
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Gold
Cable Type	RG59
Cable Diameter	6.15mm
Wire Gauge	22AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	Dual Shielding 100% aluminum/mylar foil, plus a 95% tinned copper braid

Environmental

RoHS Yes

Package Information

Package Quantity 1

Warranty Information

Warranty Limited Lifetime



Connectors

Connector A	RCA Male
Connector B	RCA Male
Connector A Diameter	12.7 mm
Connector B Diameter	12.7 mm

Cable Weights

		1.5ft	3ft	6ft	10ft	15ft	25ft	35ft	50ft
Approvals									
cUL	Yes - Cable	0.20 lbs	0.40 lbs	0.55 lbs	0.75 lbs	1.00 lbs	1.50 lbs	2.00 lbs	2.75 lbs