



Ultra-thin LCD SVGA cable HD15 M/M CL2/FT4

SVGA1-xxUT- Specifications

Description

This ultra-thin SVGA cable consists of a HD15 VGA male connector on both ends. It is typically used to connect a VGA source such as a computer or laptop to a VGA input on a LCD/LED/Plasma screen.

- Constructed of ultra thin SVGA cable designed specifically for LCD/Plasma screens
- Slim low-profile HD15 molded connectors fit well in tight spaces
- This premium double shielded construction is designed to minimize any signal loss or ghosting that may appear with lesser quality cables
- Ferrite cores placed at either end of the cable further enhance the video quality

Physical Characteristics

Color	Black
Connector Plating	Nickel
Contact Plating	Gold
Wire Gauge - Coax	3 - 32AWG Mini-Coax
Wire Gauge - Conductors	9 - 30AWG Conductors
Cable Diameter	5.7mm
Shielding	AEB Braid, 100% Mylar Foil, Ferrite Cores
Jacket Fire Rating	CL2/FT4
Jacket Material	PVC
Strain Relief	Molded PVC

Connector(s)

Connector A	Ultra-thin SVGA HD15 Male
Connector B	Ultra-thin SVGA HD15 Male

Performance

Impedance	75 ohm
-----------	--------

Approvals

c(UL)us	Approved Cable
---------	----------------

Environmental

RoHS	Yes
Reach	Yes
Conflict Minerals	Yes

Packaging Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------



Cable Weights

1ft	3ft	6ft	10ft
0.10 lbs	0.25 lbs	0.31 lbs	0.42 lbs
15ft	25ft	35ft	50ft
0.53 lbs	0.81 lbs	1.00 lbs	1.50 lbs
75ft	100ft		
2.15 lbs	2.90 lbs		