



Premium Ultra-Thin LCD SVGA + 3.5mm Audio Cable HD15 Male to Male CL2/FT4 Rated

SVGA1A-xxUT - Specifications

Description

- This ultra-thin SVGA cable consists of a HD15 male and 3.5mm stereo male on both ends. It is typically used to connect VGA outputs such as computers/laptops to VGA inputs such as VGA flat panel monitors.
- Constructed of a combination of 3 mini coax cables and 9 conductors for optimal SVGA video quality
 - This premium double shielded construction is designed to minimize any signal loss or ghosting that may appear with lesser quality cables
 - Ferrite cores placed at either end of the cable further enhance the video quality
 - Fully CL2/FT4 fire rated for in-wall use

Physical Characteristics

Color	Black
Connector Plating	Nickel
Wire Gauge - Coax	3 - 30AWG Mini-Coax
Wire Gauge - Conductors	9 - 30AWG Conductors
Wire Gauge - Audio	2C - 30AWG Conductors
Cable Diameter	6.50mm
Shielding	AEB Braid, 100% Mylar Foil, Ferrite Cores
Jacket Fire Rating	CL2/FT4
Jacket Material	PVC
Strain Relief	Molded PVC

Connectors

Connector A	1 - SVGA HD15 Male 1 - 3.5mm Stereo Male
Connector B	1 - SVGA HD15 Male 1 - 3.5mm Stereo Male

Performance

Resolution	1600 x 1200px
Impedance	75 ohm

Approvals

c(UL)us	Approved Cable
---------	----------------

Environmental

RoHS, Reach, Conflict Minerals	Yes
--------------------------------	-----

Packaging Information

Package Quantity	1 Cable
------------------	---------

Cable Weights

3ft	6ft	10ft	15ft	25ft	35ft
0.25 lbs	0.40 lbs	0.55 lbs	0.70 lbs	1.05 lbs	1.40 lbs
50ft	75ft	100ft			
1.90 lbs	2.70 lbs	3.50 lbs			

