



Cisco® 10G SFP+ Bi-Directional 1310nm/1270nm LC Transceiver - 10km

TR-SFP-10G-BXD-I - Specifications

Description

This is an Enhanced Small Form-factor Pluggable (SFP+) transceiver module with maximum data transfer rate of 10 Gbps up to 10km over singlemode fiber cable. It is used in network devices with an SFP+ slots. The transceivers are Multi-Source Agreement (MSA) compliant and built to OEM specifications.

NOTE: Each network link needs to have a up transceiver and a down transceiver. Ex./ TR-SFP-10G-BXD-I should be purchased with TR-SFP-10G-BXU-I.

Physical Characteristics

Dimensions	57mm x 15mm x 9mm (L x W x H)
Operating Temperature	0°C ~ 70°C
Storage Temperature	-40°C ~ 80°C
Laser Type	Class 1

Connectors

Connector	LC Simplex
-----------	------------

Performance

Media Supported	10GBase-LR Singlemode Fiber
Maximum Transmission Distance	10km
Wave Length	TX: 1310nm RX: 1270nm
DDM Support	Yes

Certifications

CE	Yes
FCC	Yes
RoHS	Yes

Packaging Information

Package Quantity	1
Product Weight	0.02 lbs [0.01kg]

