

Premium Phantom Cables Balanced 1/4 Inch TRS Male To 3.5mm **Locking Male Cable**

TRSM-35MML-xx - Specifications

Description

This stereo audio cable has a 1/4 inch TRS male on one end and a 3.5mm locking male on the other. It is typically used to connect instruments or equipment with stereo outputs to a wireless transmitter.

• Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance

Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible

Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility

High quality, 24K gold plated shielded connectors allows for optimum connectivity and maintains a clean signal integrity

FT4 riser fire rated jacket for in-wall use

Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color Black

Connector Plating Gold

Cable Diameter 4.0 mm

Wire Gauge 22AWG

PVC - Polyvinyl Chloride Jacket Material

Fire Rating FT4 (Riser CMR)

90% Copper Braid, 100% Mylar Foil Cable Shielding

Strain Relief Metal Shell

Connectors

3.5mm Stereo Locking Male Connector A

Connector B 1/4 Inch TRS Male

Approvals

Yes - Cable c(UL)us

Environmental

RoHS Yes **Package Information**

Package Quantity

Warranty Information

Warranty Limited Lifetime

Cable Weights

1.5ft	3ft	6ft	10ft	15ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs
25ft	35ft	50ft	75ft	100ft
1.00 lbs	1.30 lbs	1.75 lbs	3.00 lbs	3.50 lbs

