



# Premium Phantom Cables Un-balanced 1/4 Inch TS Male To 3.5mm Locking Male Cable

TSM-35MML-xx - Specifications

**Description**

This mono audio cable has a 1/4 inch TS male on one end and a 3.5mm locking male on the other. It is typically used to connect instruments or equipment with mono outputs to a wireless transmitter.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, 24K gold plated shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

**Physical Characteristics**

Color	Black
Connector Plating	Gold
Cable Diameter	60 mm
Wire Gauge	18AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	95% Copper Braid, 100% Mylar Foil
Strain Relief	Metal Shell

**Connectors**

Connector A	3.5mm Stereo Locking Male
Connector B	1/4 Inch TRS Male

**Approvals**

c(UL)us	Yes - Cable
---------	-------------

**Environmental**

RoHS	Yes
------	-----

**Package Information**

Package Quantity	1
------------------	---

**Warranty Information**

Warranty	Limited Lifetime
----------	------------------

**Cable Weights**

1.5ft	3ft	6ft	10ft	15ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs
25ft	35ft	50ft	75ft	100ft
1.00 lbs	1.30 lbs	1.75 lbs	3.00 lbs	3.50 lbs

