



Premium Phantom Cables RG59 F-Type Male to BNC Male Cable

FT4

TV-BNCPH-xx - Specifications

Description

This premium RG59 coax cable consists of a F-Type male connector on one end, and a BNC male connector on the other end. It is used to connect a CCTV output to a video display input.

- Constructed of low-loss, High Definition 75 ohm multi-stranded, heavy gauge cable for premium performance and maximum flexibility
- FPE dielectric insulation allows for a stable velocity of propagation therefore minimizing possible timing delays
- Cables nominal capacitance is an exceptional 18.6 pf/ft and has a nominal attenuation of 3.00 dB/100ft
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- Durable cable jacket is ultra flexible to maximize mobility
- High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- The connector backshells are made of a durable, zinc plated metal alloy
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Gold
Cable Diameter	6.15 mm
Wire Gauge	22AWG Stranded Bare Copper
Jacket Material	PVC - Polyvinyl Chloride
Jacket Rating	FT4 - Riser
Cable Shielding	100% aluminum/mylar foil, plus a 95% tinned copper braid
Strain Relief	Metal Shell

Connector(s)

Connector A	F-Type Male
Connector B	BNC Male

Performance

Impedance	75 Ohm
Capacitance	18.6 PF/FT
Velocity of Propagation	78%

Approvals

c(UL)us	Approved Cable
---------	----------------

Packaging Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

3ft	6ft	10ft	15ft	25ft
0.40 lbs	0.55 lbs	0.75 lbs	1.00 lbs	1.50 lbs
35ft	50ft	75ft	100ft	
2.00 lbs	2.75 lbs	4.00 lbs	5.25 lbs	

