

Premium Phantom Cables RG59 F-Type Male to RCA Male Cable FT4

TV-RCAPH-xx - Specifications

Description

This RG59 cable consists of a RCA male connector on one end and a F-type connector on the other end. It is used to connect a CCTV output to a video display input.

Constructed of low-loss, High Definition 75 ohm multi-stranded, heavy gauge cable for premium performance and maximum flexibility

1

- FPE dielectric insulation allows for a stable velocity of propagation therefore minimizing possible timing delays
- Cables nominal capacitance is an exceptional 18.6 pf/ft and has a nominal attenuation of 3.00 dB/100ft
- Dual shielding includes a 100% aluminum/mylar foil, plus a 95% tinned copper braid
- · Durable cable jacket is ultra flexible to maximize mobility
- · High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- · The connector backshells are made of a durable, zinc plated metal alloy
- · Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color Black

Connector Plating Gold

Cable Diameter 6.15 mm

Wire Gauge 22AWG Stranded Bare Copper

Jacket Material PVC - Polyvinyl Chloride

Jacket Rating FT4 - Riser

Cable Shielding 100% aluminum/mylar foil, plus a 95% tinned copper braid

Strain Relief Metal Shell

Connector(s)

Connector A F-Type Male

Connector B RCA Male

Performance Packaging Information

Yes

Impedance 75ohm Package Quantity

Capacitance 18.6 PF/FT Warranty Information

Velocity of Propagation 78% Warranty Limited Lifetime

Cable Weights

<u>Approvals</u>

RoHS

c(UL)us Approved Cable

3ft 6ft 10ft 15ft 25ft 35ft 50ft 75ft 100ft **Environmental** 0.40 lbs 0.55 lbs 0.75 lbs 1.00 lbs 1.50 lbs 2.00 lbs 2.75 lbs 4.00 lbs 5.25 lbs