



# USB 2.0 A Straight Male to A Up/Down Angle Male Cable

## USB-222-xx- Specifications

### Description

This USB 2.0 cable consists of a USB straight A male on one end and a USB A up angle or down angle A male on the other end. The angled end uses a reversible USB A male connector which allows it to be inserted in either an up angle or down angle exit. It is typically used to connect a USB peripheral to your computer such as a USB hub to a PC.

### Physical Characteristics

Color	Black
Connector Plating	Nickel Plated
Contact Plating	Gold Plated
Cable Diameter	3.5 mm
Jacket Material	PVC - Polyvinyl Chloride
Cable Shielding	100% Foil
Strain Relief	Molded PVC
Operating Temperature	0 to 45 deg C (32 to 113°F)
Storage Temperature	-10 to 80 deg C (14 to 176°F)
Cable Voltage Rating	30V

### Connector(s)

Connector A	USB 2.0 Type A Straight Male
Connector B	USB 2.0 Type A Up/Down Male

### Performance

Rating	USB 2.0 Hi-Speed Compliant Cable
Speed	480 Mbps
Compatibility	Backwards Compatible with 1.0

### Approvals

UL	Yes - Cable
cUL	Yes - Cable

### Environmental

RoHS, Reach	Yes
Conflict Minerals	Yes

### Packaging Information

Package Quantity	1
------------------	---

### Warranty Information

Warranty	Limited Lifetime
----------	------------------

### Cable Weights

1ft	3ft	6ft	10ft	15ft
0.05 lbs	0.15 lbs	0.30 lbs	0.50 lbs	0.75 lbs

