

USB 2.0 A Panel Mount Female to IDC 5-pin Header Female Hi-Speed Cable

USB-258-xx - Specifications

Description

This cable consists of a USB 'A' male on one end and a USB 'A' panel mount female on the other end. It is typically used to add an external panel mount USB connection to wall plates, kiosks or other custom solutions where a USB outlet is required.

Physical Characteristics

Color Black

Connector Plating Nickel Plated
Contact Plating Gold Plated

Cable Diameter 4.5 mm

Wire Gauge 28AWG (data) / 24AWG (power)

Jacket Material PVC - Polyvinyl Chloride

Cable Shielding 65% ALMG

Strain Relief Molded PVC

Temperature Rating 80 deg C

Cable Voltage Rating 30V

Connector(s)

Connector A IDC 5-pin Header Female

Connector B USB 2.0 Type A Panel Mount Hi-Speed Female

Performance

Rating USB 2.0 Hi-Speed Compliant Cable

Speed 480 Mbps

Compatibility Backwards Compatible with 1.0

Approvals

UL, cUL Yes - Cable

Environmental

RoHS Yes

Reach Yes

Conflict Minerals Yes

Packaging Information

Package Quantity 1

Warranty Information

Warranty Limited Lifetime

Cable Weights

6 inch 1ft 3ft 6ft

0.05 lbs 0.07 lbs 0.10 lbs



0.15 lbs



USB 2.0 A Panel Mount Female to IDC 5-pin Header Female Hi-Speed Cable

USB-258-xx - Specifications









