


# HDMI Wall Plate Extender Over Cat5e/6 UTP Cable 60M - IR & 3D support

This HDMI single Cat5e/6 wall plate videoextender allows you to extend your HD display up to 190ft (60 meters) and keepsyour cables hidden behind walls. Built-in IR extender function allows IR remotecontrol of source devices from remote viewing location by sending IR commands received in the area of the display back to the source devices. Power isrequired at both the transmitter and receiver units.

Physical Characteristics	
Color	White
Wall Plate Size	Single Gang
Dimensions (LxWxH)	115x70x35mm
Operating Temperature Range	-5°c ~ 35°c
Power	
Power Supply	DC 5 volts p-p(TTL)
Power Consumption	3 Watts (maximum)
Compatibility	
PC to Monitor	Yes
PC to TV	Yes
DVD to Monitor	No
DVD to TV	Yes
Connector(s)	
Transmitter	HDMI Female (Input), RJ45 Ethernet interface, IR (3.5 mm) in/out, 5V DC in
Receiver	HDMI Female (Output), RJ45 Ethernet interface, IR (3.5 mm) in/out, 5V DC in
Performance	
Video Format	DTV/HDTV: 480i/ 567i/ 480p/ 567P/ 720p/ 1080i/ 1080p@60Hz 3D video format
Video Bandwidth	Maximum TMDS clock frequency 165Mhz (4.95Gbps)
Transmission Range	1080p 8-bit 30m (maximum); 1080p 12-bit 25m (maximum) over CAT5E/CAT6 / 24AWG/ Solid (recommended to use 23AWG Cat6 cable)
Audio	8-channel, supports Dolby True HD and DTS Master
HDCP Compliant	Yes
Bi-direction remote	Yes
CEC pass through	Yes
EDID Call Back	Yes
Indicator Light	Power Green, video link yellow
Remote IR	Wavelength: 940nm, Frequency: 38KHz
Environmental	
RoHS	Yes
Certification(s)	
CE	Yes
FCC	Yes



Name	HDMI Wall Plate Extender Over Cat5e/6 UTP Cable 60M - IR & 3D support
P/N	VE-HDMI-011



Name	HDMI Wall Plate Extender Over Cat5e/6 UTP Cable 60M - IR & 3D support
P/N	VE-HDMI-011