

2-Port HDMI 2.1 Bi-directional Splitter/ Switch, 8K - HDR - Dolby Vision VPW-100-02 - Specifications

Description

This 1x2 bi-directional HDMI 2.1 splitter/switch enables you to display one HDMI device to two HDMI displays (mirrored) simultaneous. It is typically used to connect a HDMI source such as DVD player, Blu-ray player, satellite receiver or gaming system to HDMI displays such as UHD TVs, HD projectors or HDMI monitors. The device could also function as a switch, allowing 2 separate UHD sources to be sent to 1 UHD display. A push button on the device controls which source is being displayed. The splitter/switch performs at HDMI 2.1 resolutions - 8K at 60Hz with transmit bandwidth up to 48Gbps. It also supports HDCP 2.3 and is backward compatible.

Physical Characteristics

| Dimensions | 56mm x 53mm x 20.8mm | | |
|------------------------|--|-------------------------|-------------------------------------|
| Compatibility | | | ST PT |
| PC to Monitor | Yes | | 5 th and a second second |
| PC to TV | Yes | | 55 ²⁰ |
| DVD to Monitor | Yes | | HOMA |
| DVD to TV | Yes | | |
| Connector(s) | | | A B HOMB |
| Input | 1 x HDMI Female | | |
| Output | 2 x HDMI Female | | |
| Performance | | | |
| Video Format | 480P/720P/1080P/2160P@120/60/50/30/25/24 4320@60/50/30/25/ | /24 Supports HLG/HDR/HD | R10/HDR10+ and Dolby Vision |
| Deep Color | 8/10/12/16Bit@2160P ,8/10bit@4320 | | |
| Audio Format | Dolby HD/DTS HD/Dolby Atoms/Dolby AC3/DTS/LPCM | | |
| HDCP Compliant | Yes, Supports HDCP2.2/1.4 | | |
| Transmission Bandwidth | 1.2GHz Max. | | |
| Transmission Rate | 48Gbps Max. | | |
| Max Working Current | 400mA | | |
| Working Temperature | -5 ~ +40℃ | | |
| Working Humidity | 5 to 85%RH (No Condensation) | | |
| Storage Temperature | -15 to 55℃ | | |
| Storage humidity | 5 to 95%RH (No Condensation) | | |
| Approvals | | Packaging Information | |
| CE | Yes | Included in Package | 1 - HDMI Switch |
| Environmental | | | 1 - Micro USB External Power Supply |
| RoHS | Yes | Weight | 0.19lbs |