



# Premium Phantom Cables XLR Female to 2x XLR Male Balanced Splitter Cable

## XLR-FMM-xx - Specifications

**Description**

This splitter cable has an XLR female on one end and two XLR males on the other. It is typically used to split a microphone or XLR output into two duplicate balanced channels.

- Two separate 24AWG cables breakout directly from the source connector
- Breakout begins directly from the source connector
- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra-flexible to maximize mobility
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

**Physical Characteristics**

Color	Black
Connector Plating	Nickel
Contact Plating	Gold
Cable Diameter	5.0mm
Wire Gauge	24AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Bare Copper Braid, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

**Connectors**

Connector A	XLR Female
Connector B	XLR Male
Connector C	XLR Male

**Approvals**

cUL	Yes - Cable
-----	-------------

**Environmental**

RoHS	Yes
------	-----

**Package Information**

Package Quantity	1
------------------	---

**Warranty Information**

Warranty	Limited Lifetime
----------	------------------

**Cable Weights**

1.5ft	3ft	6ft	10ft	15ft	25ft	35ft	50ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs	1.00 lbs	1.30 lbs	1.75 lbs

