



Premium Phantom Cables XLR Male to 2x XLR Female Balanced Splitter Cable

XLR-MFF-xx - Specifications

Description

This splitter cable has an XLR male on one end and two XLR females on the other. It is typically used to split a microphone or XLR output into two duplicate balanced channels.

- Two separate 24AWG cables breakout directly from the source connector
- Breakout begins directly from the source connector
- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra-flexible to maximize mobility
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Nickel
Contact Plating	Gold
Cable Diameter	5.0mm
Wire Gauge	24AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Bare Copper Braid, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

Connectors

Connector A	XLR Male
Connector B	XLR Female
Connector C	XLR Female

Approvals

cUL	Yes - Cable
-----	-------------

Environmental

RoHS	Yes
------	-----

Package Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

1ft	3ft	6ft	10ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs