



# Premium Phantom Cables XLR Male to 2x XLR Male Balanced Splitter Cable

XLR-MMM-xx - Specifications

## Description

This splitter cable has an XLR male on one end and two XLR males on the other. It is typically used to split a microphone or XLR output into two duplicate balanced channels.

- Two separate 24AWG cables breakout directly from the source connector
- Breakout begins directly from the source connector
- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra-flexible to maximize mobility
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

## Physical Characteristics

Color	Black
Connector Plating	Nickel
Contact Plating	Gold
Cable Diameter	5.0mm
Wire Gauge	22AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Bare Copper Braid, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

## Connectors

Connector A	XLR Male
Connector B	XLR Male
Connector C	XLR Male

## Approvals

cUL	Yes - Cable
-----	-------------

## Environmental

RoHS	Yes
------	-----

## Package Information

Package Quantity	1
------------------	---

## Warranty Information

Warranty	Limited Lifetime
----------	------------------

## Cable Weights

1ft	3ft	6ft	10ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs

