



Premium Phantom Cables XLR Female To 3.5mm Male Balanced
Audio Cable FT4

XLRF-35MM-xx - Specifications

Description

This premium stereo audio cable has a XLR female on one end and a 3.5mm male on the other. It is typically used to connect a microphone to an audio input such as on a PC or video camera.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, heavy duty shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

| | |
|-------------------|---|
| Color | Black |
| Connector Plating | Gold |
| Cable Diameter | 5.0mm |
| Wire Gauge | 24AWG |
| Jacket Material | PVC - Polyvinyl Chloride |
| Fire Rating | FT4 (Riser CMR) |
| Cable Shielding | 100% Aluminum-Mylar Foil, 90% Bare Copper Braid |
| Strain Relief | Metal Shell |

Connectors

| | |
|-------------|-------------------|
| Connector A | 3.5mm Stereo Male |
| Connector B | XLR Female |

Approvals

| | |
|-----|-------------|
| cUL | Yes - Cable |
|-----|-------------|

Environmental

| | |
|------|-----|
| RoHS | Yes |
|------|-----|

Package Information

| | |
|------------------|---|
| Package Quantity | 1 |
|------------------|---|

Warranty Information

| | |
|----------|------------------|
| Warranty | Limited Lifetime |
|----------|------------------|

Cable Weights

| 1.5ft | 3ft | 6ft | 10ft | 15ft | 25ft | 35ft | 50ft |
|----------|----------|----------|----------|----------|----------|----------|----------|
| 0.30 lbs | 0.35 lbs | 0.45 lbs | 0.55 lbs | 0.70 lbs | 1.00 lbs | 1.30 lbs | 1.75 lbs |

