



Premium Phantom Cables Balanced XLR Female to mini-XLR Male Cable

XLRF-MM-xx - Specifications

Description

This premium stereo audio cable has an XLR female connection on one end and a Mini-XLR male connection on the other end. It is typically used to connect microphones to wireless audio devices or as a condenser microphone cable.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Spiral shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Nickel
Contact Plating	Gold
Cable Diameter	2.8mm
Wire Gauge	28AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	85% Spiral Shield, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

Connectors

Connector A	1 - Mini-XLR Male
Connector B	1 - XLR Female

Approvals

c(UL)us	Yes - Cable
---------	-------------

Environmental

RoHS	Yes
------	-----

Package Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

3ft	6ft	10ft	15ft	25ft
0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs	1.00 lbs
35ft	50ft	75ft	100ft	
1.30 lbs	1.75 lbs	2.50 lbs	3.25 lbs	

