



Premium Phantom Cables Mini-XLR Female To 3.5mm Locking Male Cable

XLRFM-35MML-xx - Specifications

Description

This audio cable has a mini-XLR female on one end and a 3.5mm locking male on the other. It is typically used to connect a headset or lav microphone to a wireless transmitter or camera.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, 24K gold plated shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Connector Plating	Gold
Cable Diameter	2.8 mm
Wire Gauge	28AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Copper Braid, 100% Mylar Foil
Strain Relief	Metal Shell

Connectors

Connector A	3.5mm Stereo Locking Male
Connector B	Mini-XLR Female

Approvals

c(UL)us	Yes - Cable
---------	-------------

Environmental

RoHS	Yes
------	-----

Package Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

	1.5ft	3ft	6ft	10ft	15ft
	0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs
	25ft	35ft	50ft	75ft	100ft
	1.00 lbs	1.30 lbs	1.75 lbs	3.00 lbs	3.50 lbs

