



## Premium Phantom Cables XLR Male to BNC Male Unbalanced Cable

XLRM-BNC-xx- Specifications

### Description

This premium time code cable has a XLR male on one end and a BNC male on the other. It is typically used in time code applications on professional video cameras.

### Features:

- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, gold plated, heavy duty shielded connectors optimizes connectivity and maintains a clear signal integrity
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

### Physical Characteristics

Length	1.5 / 3ft / 6ft / 10ft / 15ft / 25ft / 35ft / 50ft
Color	Black
Contact Plating	Gold
Cable Diameter	5.0mm
Wire Gauge	22AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	90% Bare Copper Braid, 100% Aluminum Mylar Foil
Strain Relief	Metal Shell

### Connectors

Connector A	1 - BNC Male
Connector B	1 - XLR Male

### Approvals

cUL	Yes - Cable
-----	-------------

### Environmental

RoHS	Yes
------	-----

### Packaging Information

Package Quantity	1
------------------	---

