



Premium Phantom Cables XLR Male to 1/4 inch TRS Male Balanced Audio Cable FT4

XLRM-TRSM-xx - Specifications

Description

This balanced interconnect audio cable has a XLR male on one end and a 1/4 inch TRS male on the other. It is typically used to connect a XLR input to a balanced 1/4 inch TRS output.

- Hi-flex balanced cable is used to capture all highs & lows for optimum audio performance
- Braided shield surrounds center conductors for maximum EMI/RFI noise rejection therefore maintaining the cleanest signal possible
- Multi-stranded copper center conductors and a durable cable jacket is ultra Flexible to maximize mobility
- High quality, heavy duty shielded connectors allows for optimum connectivity and maintains a clean signal integrity
- FT4 riser fire rated jacket for in-wall use
- Lead Free, "silver laced" solder is used in order to reduce loss and maximize conductivity

Physical Characteristics

Color	Black
Contact Plating	Gold
Cable Diameter	5mm
Wire Gauge	22AWG
Jacket Material	PVC - Polyvinyl Chloride
Fire Rating	FT4 (Riser CMR)
Cable Shielding	100% Aluminum-Mylar Foil, 90% Bare Copper Braid
Strain Relief	Metal Shell

Connectors

Connector A	XLR Male
Connector B	1/4 Inch TRS Male

Approvals

cUL	Yes - Cable
-----	-------------

Environmental

RoHS	Yes
------	-----

Package Information

Package Quantity	1
------------------	---

Warranty Information

Warranty	Limited Lifetime
----------	------------------

Cable Weights

1.5ft	3ft	6ft	10ft	15ft	25ft	35ft	50ft
0.30 lbs	0.35 lbs	0.45 lbs	0.55 lbs	0.70 lbs	1.00 lbs	1.30 lbs	1.75 lbs

