




## Adjusting & Bleeding Your New Brake Conversion

A. Caliper ear with sliding mounting sleeve.


B. Slide sleeve inboard and on two-piece brackets add or subtract spacers between base and top bracket to put the welded sleeve of the top bracket close to the ear of the caliper.

**\*\*YOU MUST ADJUST PARKING BRAKE FIRST \*\* ON THE ROTOR\*\*BEFORE YOU BLEED THE BRAKES**


1. When you install the calipers put them in the position you like. One where the cable will work well (if you have the park brake calipers) and the hose connection is in a good location. If you go off road you can mount the calipers high to avoid brush and rocks. Don't worry about being in the right position to bleed the brakes. The calipers have to be taken off of the brackets to bleed anyway and once they are bled it does not matter what position they are in.
2. Torque the caliper pins 17-22 FT pounds do not over torque.
3. Adjust the parking brake levers by pushing them forward all the way. Do this manually not with your park brake cables. Each time you push them they should move off of the stop less. To be properly adjusted, they should only move off of the stop 1/4 inch. When released, they should always return to the stop. If they will not adjust, try putting a lever between the rotor and the pad and putting pressure on the piston. Now push the lever releasing pressure on the pad as the caliper adjusts. These are the only two ways we know of to adjust the parking brake. If the calipers won't adjust you will have a low pedal because the piston will retract too far and will use up all your hydraulic pedal travel to put the brakes on.
4. Before you put the wheels on, bleed the calipers. Air rises so the bleed screw must be at the top. You can start by the normal bleeding methods, but the brakes will not work properly and you will have a soft pedal if you do not take the calipers off of the brackets and gravity bleed them to get the last of the air out.



5. To gravity bleed take the cover off of the master cylinder, take the calipers off of the brackets, and hold behind the axle. Hold the caliper so that the bleed screw points forward, horizontal with the ground on the (small) 5 1/2 inch pin to pin calipers and straight up on the (large) 7 inch pin to pin calipers. The mounting holes in the ears are around 45 degrees on a non-parking brake caliper and straight up one hole above the other on a parking brake caliper. Open the bleed screw and the fluid will start to dribble out. Slowly move the calipers just in case you are not in the correct position and also tap on the calipers with a rubber hammer to knock bubbles loose. Once the fluid is clear with no air bubbles close the bleeder and hang that caliper on a wire and do the other side. Do both calipers again and then reinstall.



6. Once the parking brake calipers are adjusted put a c-clamp between the lever and the bracket to hold the parking brakes locked up. Step on the hydraulic pedal it should be high and hard. If it is low and spongy, or it will pump up, you still have air. Take the caliper off the brackets and bleed some more. If you have parking brake calipers, and they are locked up against the rotors and there is no air in the rear system. Then there will be no fluid movement in the rear brake system and the pedal should be as high as before you changed the brakes and had the parking brake on. It does not matter what size master cylinder you have if there is no fluid movement you will have a high and hard hydraulic pedal. There might be a problem with your front system since you have a dual braking system. But if you have not changed the front, your pedal should be high and hard. It is not as easy to check if you are using non-parking brake calipers. The calipers run close to the rotors, so check to see that the pads won't rattle. If your pedal is low and spongy, you have air. Take the calipers off and bleed them some more.



7. Remove the springs off of your stock cables. It is too much spring with the springs also on the caliper arms. Also, the stock springs will coil bind.

**8. You must use parking brake at minimum once a month to keep in adjustment as pads wear.**

**9. The parking brake caliper pistons are a screw design, DO NOT compress with a "C" clamp. They must be screwed back in to reset.**