Factory Option










Seed Beads Device

Automatic color changing seed beads embroidery device By automating beads embroidery which was previously performed manually by craftsmen, mass production has







i-TM realizes thread tension that coincides with the characteristic of each stitch. By controlling the upper thread consumption volume, the digitally controlled motor provides the appropriate tension. As a result, problems such as the under thread coming out on the top of the fabric, the fabric becoming wrinkled, etc. are solved, and the unevenness of the embroidery finish for every head is prevented.





ESQ-C (Easy Sequin Device Color Change Type)

After simplifying the complicated application of sequins on a large scale, quality improvement and the minimizing of adjustment time has been realized. It has become much easier to change the type and size of sequin at will. The linked bead attachment can also be added as an option.





SBC (Smart Bobbin Changer)

Replacement bobbins are held and set into their respective rotary hooks. Completed in only 6 seconds!!

It takes the SBC only 6 seconds to replace the bobbins on all heads. Because replacement bobbins can be set beforehand while the embroidery machine is in operation, the downtime of the machine due to bobbin replacement can be drastically reduced.

	I	0000000 00000000		E			
Model	Needles	Multicolor heads	Head interval	Embroidery space [mm] D × W	A	В	С
TMCR-V0620F(550×200)D	6	20	200D	550 × 200(400)	5,365	1,610	1,635
TMCR-V0918F(800×400)S	9	18	400S	800 × 400	8,565	2,080	1,635
TMCR-V0918F(1,200×400)D	9	18	400D	1,200 × 400(800)	9,055	2,880	1,735
TMCR-V0920F(680×330)S	9	20	330S	680 × 330	7,915	1,820	1,635
TMCR-V0930F(1,500×240)DE	9	30	240DE	1,500 × 240(480)	8,905	3,480	1,635
TMCR-V1212F(680×345)S	12	12	345S	680 × 345	5,455	1,820	1,635
TMCR-V1215F(680×400)S	12	15	400S	680 × 400	7,365	1,820	1,635

Contact us for other specifications and more details

Specifications

Mainshaft motor : AC servo motor X and Y axis motor: AC servo motor Revolution: Max. 1,100 rpm Power consumption: 1,2 kw


Power supply : 3-phase 200-240 / 380 / 415V 50/60Hz

Single-phase 200-240V

Factory options: Automatic Lubrication system, Automatic Frame Changer, SBC (Smart Bobbin Changer), UBCII (Bobbin Changer II), ESQ-C (Easy Sequin Device Color Change Type),

Sequin Device IV, Seed Beads Device, i-TM

Dealer options: Multi Cording Device 2, Boring Device 2, Beam Sensor, Position Marker



Please contact our distributor listed belo

Tajima Industries Ltd.

19-22, Shirakabe 3-chome, Higashi-ku Nagoya 461-0011 JAPAN TEL. +81-52-932-3444, 3445 FAX. +81-52-932-2457, 3449





TISM Co.,Ltd.





* The specifications and designs of our products are subject to change without notice for performance improvemen



ELECTRONIC MULTI-HEAD AUTOMATIC EMBROIDERY MACHINE

The ultimate flagship model with unsurpassed flexibility powered by sophisticated features.





Fashioning your Future Tajima always leads, never follows



Features


Incorporation of the Digitally Controlled Presser Foot for secure fabric stability.



The DCP can reduce fabric fluttering that occurrs during embroidery.

It is especially effective when embroidering on thick fabric, thin fabric and folds of sewn fabric.







In addition, the DCP can position the presser foot to the most suitable height according to the thickness of the fabric. The work which would normally be carried out by a skilled person can be easily set on the touch panel.




*DCP stands for "Digitally Controlled Presser foot".

FS mode to expand material variations.



The FS mode is standardly equipped on all models. The FS Mode dramatically improves the quality of embroidery done with thick or soft-twisted thread that was unsuitable for embroidery machines in the past.















- · Options for more beautiful embroidery of soft-twisted thread.
- The rotation speed is limited when using the FS mode.

Direct command switches

Various operation switches and multi-color LEDs are located on each tension base.

Since all of the main functions of the operation panel can be manipulated at each head, operator work efficiency has been improved. Commonly used functions may be assigned to the custom switches. (Scheduled for 2018)





Multi Cording Device 2 (Dealer Option)





Tajima's original Multi Cording Device 2 allows you to sew six kinds of cord. The material can be sewn precisely by using the digitally controlled presser foot which presses with the power and timing suitable for the material. Maintaining the texture of the material, softer material is finished softly, and it is possible to embroider with a three-dimensional impression when sewing while overlapping the cord.



