



Extra Heavy Blockout No. 10

A heavy, non-flammable, water-soluble blockout for use with coarse mesh counts.

The high viscosity of No. 10 affords easier handling, and generally assures effective coverage in a single coating. Especially useful with coarse mesh. Can be used for touchups when thinned with cold water. Can be used in unventilated rooms since it contains no organic solvents. *Recommended for use on all fabrics, with all stencil systems.*
Use only with non-aqueous inks.

INSTRUCTIONS:

For direct emulsion and CDF® Direct-Film stencils: Pour a small amount of Extra Heavy Blockout No. 10 onto the open border area of the fully processed and dried stencil on the substrate side of the screen. Scrape it evenly into the fabric, using a piece of cardboard or plastic. Use the scraper to smooth and thin the layer to promote quick drying.

For Indirect System stencils: For best register and a strong “knit” between stencil and blockout, apply the Extra Heavy Blockout No. 10, as above, when the screen fabric is dry, but before the film is completely dry. Apply the blockout to the substrate side of the screen, going over the edges of the backing sheet. Let the stencil and Extra Heavy Blockout No. 10 dry completely before printing.

For touchups: Thin No. 10 with cold water and touch up as needed.

To remove: After ink removal, but before stencil removal, rinse with water.

PACKAGING: 1 quart=946 ml 1 gallon=3.785 liters 5 gallons=18.925 liters 50 gallons=189.25 liters