

# SAFETY DATA SHEET



SDS No.: 1.0  
Revision: N/A  
Date Created: February 20, 2020

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** RB Screen Wash  
**General Use:** Cleaner  
**Product Description:** Clear, light yellow Liquid

**Manufactured By:**  
Easiway Systems, Inc.  
540 S River Street  
Delano, MN 55328  
Phone 1-763-972-6306  
[www.easiway.com](http://www.easiway.com)  
[sales@easiway.com](mailto:sales@easiway.com)

**Distributed By:**  
RB Digital  
6325 Dixie Rd. Unit 7  
Mississauga, ON L5T 2E5  
Phone: 416.638.0638  
<https://rbdigital.ca/>

**EMERGENCY TELEPHONE NUMBER:**  
(800)-255-3924 ChemTel USA, Canada, Puerto Rico  
& U.S. Virgin Islands  
+1(813) 248-0585 ChemTel International (Call Collect)  
**Easiway Systems Contract Number MIS3609005**

## 2. HAZARD IDENTIFICATION

### EMERGENCY OVERVIEW

#### GHS CLASSIFICATION OF SUBSTANCE

<b>Flammable Liquid</b>	Category 4 - Combustible
<b>Aspiration Toxicity</b>	Category 1
<b>Skin Corrosion/Irritation</b>	Category 2
<b>Eye Corrosion/Irritation</b>	Category 1
<b>Carcinogenicity</b>	Not Rated Under GHS
<b>Specific Organ Toxicity Repeated Exposure</b>	Not Rated Under GHS
<b>Specific Organ Toxicity Single Exposure</b>	Category 3 - Respiratory System
<b>Reproductive Toxicity</b>	Not Rated Under GHS
<b>Acute Toxicity</b>	Not Rated Under GHS
<b>Germ Cell mutagenicity</b>	Not Rated Under GHS
<b>Corrosive to Metals</b>	Not Rated Under GHS
<b>Hazardous to the aquatic environment</b>	Category 2 - Acute

Hazard Category - means the division of criteria within each hazard class, e.g. acute toxicity includes five hazard categories and flammable liquids include four hazard categories. These categories compare hazard severity within a hazard class. "GHS Classification of Substance" means the material hazard class under that particular category and should not be taken as a comparison of hazard categories more generally. Degree of severity under GHS is "1" being the most severe and sequential numbers indicating correspondingly less severity. "Not Classified Under GHS" does not have characteristics that fall into any of the categories for that hazard class.

# SAFETY DATA SHEET

## GHS LABEL ELEMENTS

### Hazard Pictograms:



aspiration

eye

skin

### Signal Word:

**DANGER**

### Hazard Statements:

**H318 - Causes serious eye damage**

**H315 - Causes skin irritation**

**H304 - May be fatal if swallowed and enters airways**

**H227 - Combustible liquid**

**H401 - Toxic to aquatic life**

### Precautionary Statements

#### General:

P101-If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103-Read label before use.

#### Prevention:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves. Wear eye or face protection.

P264 - Wash hands thoroughly after handling.

#### Response:

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of water with a neutral soap.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

#### Storage/Disposal:

P403+235+404-Store in well-ventilated place. Keep cool. Store in closed container.

P501-Dispose of contents/container in accordance with local/regional/federal regulations.

**Other hazards which do not result in classification for Hazards**

**None Known**

**Not Otherwise Classified (HNOC) and Physical Hazards Not Otherwise Classified (PHNOC)**

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Substance/mixture:</b>	Mixture
<b>Other means of identification:</b>	None
<b>CAS number for mixture:</b>	Not Applicable
<b>Product Code:</b>	Screen Wash

<b>Component</b>	<b>wt%</b>	<b>CAS Registry #</b>
Diethylene glycol butyl ether	12 - 17	112-34-5
Di (propylene glycol) methyl ether acetate	12 - 18	88917-22-0
Distillates, petroleum hydrotreated light	6 - 9	64742-47-8
Polyoxyethylenealkylether	9 - 10	84133-50-6
Dimethyl Adipate	9 - 20	627-93-0
Dimethyl Glutarate	28 - 39	1119-40-0
Dimethyl Succinate	9 - 20	106-65-0

There are no additional ingredients present which, with the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

# SAFETY DATA SHEET

---

## 4. FIRST AID MEASURES

### DESCRIPTION OF NECESSARY FIRST AID MEASURES

#### **INHALATION:**

Remove to fresh air and keep at rest in a comfortable position. Get medical attention if symptoms persist after moving to fresh air. Give oxygen if available, symptoms persist, and medical attention is not immediate.

#### **EYE CONTACT:**

Remove contact lens (if present). Rinse eyes immediately with plenty of clean water for at least 15 minutes. If necessary, gently hold the eyelid open during the flush. Seek medical attention following initial eye washing. If irritation persists after the 15 minute eye washing, seek medical attention.

#### **SKIN CONTACT:**

Immediately wash skin with mild soap solution to remove material from skin. Remove affected clothing and launder prior to re-use. If skin damage occurs other than redness, seek medical attention and provide this SDS to attending medical personnel.

#### **INGESTION:**

Product is an aspiration hazard. Do NOT induce vomiting if ingested in any measureable quantity. This is not a likely route of exposure unless accidental.

### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

#### Potential acute health/effects:

Eye Contact Serious eye irritant and may cause irreversible damage if left in the eye

Inhalation Dizziness, drowsiness if inhaled in large quantities

Skin Contact Dryness and irritation; prolonged repetitive contact may cause dermatitis

Ingestion Aspiration hazard; can cause chemical pneumonitis if aspirated in the lungs

#### Over-exposure signs/symptoms

Eye Contact Physical irritation and redness

Inhalation Dizziness and drowsiness

Skin Contact Redness and dryness

Ingestion Possible indigestion

#### Indication of Immediate Medical Attention and Special Treatment Needed, if Necessary:

Notes to physician

If ingested, do not induce vomiting as the product contains petroleum distillates. Product is primarily an irritant.

Product contains both solvents and surfactants enhancing eye irritation and skin irritation at lower exposure levels.

Specific treatments No specific treatment

Protection of First-Aiders No special precautions required

---

## 5. FIRE FIGHTING MEASURES

Flashpoint and Method: 86.4°C

Flammable Limits: Not Determined

Autoignition Temperature: Not Determined

#### **GENERAL HAZARD:**

The product is combustible and will contribute fuel to a fire. The product contains dibasic acids which are esters and react with oxidizers and caustics to liberate hydrogen under certain conditions.

#### **SUITABLE EXTINGUISHING MEDIA:**

Dry chemical fire extinguishers; carbon dioxide fire extinguishers; foam; alcohol resistant foams (ATC) type. Use water fog or fine spray for cooling exposed containers to control heating.

# SAFETY DATA SHEET

## UNSUITABLE EXTINGUISHING MEDIA:

Any type of oxidizer or caustic containing extinguishing media is not advised.

## SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

The product contains solvents and surfactants. No highly toxic contaminants are expected.

## HAZARDOUS THERMAL DECOMPOSITION PRODUCTS

During a fire, smoke may contain the original material in addition to combustion products which are likely to be irritating to the respiratory tract.

## SPECIAL PROTECTIVE ACTIONS FOR FIRE FIGHTERS

Keep containers cool. Product will contribute fuel to an already existing fire and needs to be kept cool.

## SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTING

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. For small outdoor fires which may be easily extinguished with a portable fire extinguisher, use of any SCBA may not be necessary.

---

## 6. ACCIDENTAL RELEASE MEASURES

### LAND SPILL RESPONSE:

Absorb small spills with inert material such as sand or earth. Containerize waste material. Dike large spills to contain the area of the spill. Use clean up procedures that minimize contamination to earth or water bodies.

### WATER SPILL:

Product is solvent based and can be separated from the water. Skim off what can be removed from the water using systems designed for removing organic materials from water in spill situations. Take measures to avoid more extensive contamination of the water body by using adsorbent booms that don't add to a fire hazard.

### RECOMMENDED DISPOSAL:

Disposal options may be dictated by other materials mixed with this material. Dispose of in accordance with local, state, and federal regulations using methods which consider recycling/reclamation. Material is solvent based and should not be sewered for disposal.

---

## 7. HANDLING AND STORAGE

### Precautions for safe handling Protective measures

Don appropriate personal protective equipment per Section 8 of this SDS. Do not handle until all safety precautions have been read and understood. Do not get into eyes or on skin or clothing. Do not use in an area without ventilation. Keep in original container or a manufacturer approved alternate. Keep container tightly closed when not in use. Store away from caustics, oxidizers, and acids. Store under ambient conditions (close to 21°C) and atmospheric pressure.

### Advice on general occupational hygiene

Eating, drinking, and smoking is prohibited when working with this product. Workers should wash hands prior to leaving work area and eating, drinking, or smoking

### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store away from oxidizers, acids, and caustics. Keep container tightly closed when not in use.

# SAFETY DATA SHEET

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### CONTROL PARAMETERS

### OCCUPATIONAL EXPOSURE LIMITS

Substance	Exposure Limit		
Petroleum distillates, hydrotreated light	Federal Government -	TWA: 8 hrs.	STEL :
	CA Alberta Provincial -	TWA: 8 hrs.	STEL :
	CA British Columbia Provincial -	TWA: 8 hrs.	STEL :
	CA Manitoba Provincial -	TWA: 8 hrs.	STEL :
	CA New Brunswick Provincial -	TWA: 8 hrs.	STEL :
	CA Newfoundland & Labrador Provincial -	TWA: 8 hrs.	STEL :
	CA Northwest Territories Territory -	TWA: 8 hrs.	STEL :
	CA Nova Scotia Provincial -	TWA: 8 hrs.	STEL :
	CA Nunavut Territory -	TWA: 8 hrs.	STEL :
	CA Ontario Provincial -	TWA: 8 hrs.	STEL :
	CA Prince Edward Island Provincial -	TWA: 8 hrs.	STEL :
	CA Quebec Provincial -	TWA: 8 hrs.	STEL :
	CA Saskatchewan Provincial -	TWA: 8 hrs.	STEL :
	CA Yukon Territory -	TWA: 8 hrs.	STEL :
Diethylene glycol butyl ether	Federal Government -	TWA: 10ppm 8 hrs.	STEL :
	CA Alberta Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA British Columbia Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Manitoba Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA New Brunswick Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Newfoundland & Labrador Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Northwest Territories Territory -	TWA: 10ppm 8 hrs.	STEL :
	CA Nova Scotia Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Nunavut Territory -	TWA: 10ppm 8 hrs.	STEL :
	CA Ontario Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Prince Edward Island Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Quebec Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Saskatchewan Provincial -	TWA: 10ppm 8 hrs.	STEL :
	CA Yukon Territory -	TWA: 10ppm 8 hrs.	STEL :

### OCCUPATIONAL EXPOSURE LIMITS - OTHER

Component	NIOSH REL	AIHA WEEL	Other
Petroleum distillates, hydrotreated light			140 mg/m <sup>3</sup> /DFG MAK
Dipropylene glycol butyl ether	100 ppm	50 ppm	

### APPROPRIATE ENGINEERING CONTROLS:

Provide adequate general and local exhaust ventilation to maintain levels below established exposure limits. Provide eyewash stations and safety showers if it is used in a fixed facility to material users if routinely using the product. Provide hand washing facilities for routine use by personnel using the material.

### ENVIRONMENTAL EXPOSURE CONTROLS

Depending on how this product is used in the facility, direct exhaust may be a consideration. Verify that exhaust ventilation is maintaining product levels below exposure limits. Verify any waste stream from this product is characterized and accumulated in a manner compliant with the local jurisdiction away from other incompatible materials

# SAFETY DATA SHEET

## INDIVIDUAL PROTECTION MEASURES

### Hygiene Measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, and using the lavatory and at the end of the work period. Ensure eye wash stations are in close proximity to the work area. Provide hand wash facilities.

### Eye/face Protection

Splash goggles and apron should be worn when pouring this material to avoid contact with the liquid. Hand protection is recommended when there is possible direct contact with the liquid. Glove choice should be appropriate for the chemical blend and the specific activity being performed. NOTE: nitrile gloves are a general purpose glove available in a wide variety of thicknesses and protect against most chemicals.

### Skin Protection

Gloves to the elbow are recommended when pouring a large volume of the liquid. Choose a glove material that is designed for hydrocarbon and glycol ether-type solvent use.

### Body Protection

Skin protection depends on the extent of potential exposure and conditions of use. Full body solvent resistant coveralls may be required for certain uses and for clean up of spills.

### Respiratory Protection

Is required is the airborne levels are expected to approach or exceed exposure standards. Use respiratory protection appropriate for solvents.

### EXPOSURE EVALUATION:

Exposures depend on activities being performed and the ventilation in the area.

Personal exposure monitoring can be performed by the employer to determine his/her employee exposures to the product during routine use at the facility. It is beyond the responsibility of the product supplier to estimate/determine airborne exposure in a user's facility.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Vapor Pressure:</b>	Not Determined	<b>Vapor Density:</b>	Heavier than air
<b>Specific Gravity:</b>	1.04	<b>Evaporation Rate:</b>	Not Determined
<b>Solubility in Water:</b>	insoluble	<b>Freezing Point:</b>	Not Determined
<b>Melting Point:</b>	<b>Not Applicable</b>	<b>Odor:</b>	Mild
<b>pH:</b>	Not Applicable	<b>Appearance:</b>	light yellow clear
<b>Boiling Point:</b>	Not Determined	<b>Physical State:</b>	liquid
<b>Viscosity:</b>	Not Determined	<b>Flammable Range:</b>	Not Applicable
<b>Flash Point:</b>	86.4°C (Closed Cup)	<b>VOC content:</b>	Not Applicable
<b>Decomposition temp:</b>	Not Determined	<b>Odor Threshold</b>	Not Determined
<b>Partition coefficient:</b>	Not Determined		
<b>n-octanol/water</b>	Not Determined		

---

## 10. STABILITY AND REACTIVITY

### REACTIVITY

No dangerous reactions known under normal use conditions.

### CHEMICAL STABILITY

This product is stable.

### POSSIBILITY OF HAZARDOUS REACTIONS

# SAFETY DATA SHEET

## INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong acids, strong bases, and strong oxidizers. Dibasic acids are esters. Esters react with acids to liberate heat along with alcohols and acids. Strong oxidizing agents may cause a vigorous reaction that is sufficiently exothermic to ignite the reaction products. Heat is also generated by the interaction of esters with caustic solutions. Flammable hydrogen is generated by mixing esters with alkali metals and hydrides.

## CONDITIONS TO AVOID

Store product with other flammable solvent based materials in a ventilated space with secondary containment. Do not store with acids, bases, or oxidizers.

## INCOMPATIBLE MATERIALS

Acids, bases, and oxidizers.

## HAZARDOUS DECOMPOSITION PRODUCTS:

Hydrogen is created when exposed to hydrides and alkali metals. Otherwise product is stable and no decomposition will occur.

---

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

<u>Component</u>	<u>Acute Test</u>	<u>Value</u>	<u>Species</u>
Petroleum distillates, hydrotreated light	LD50 oral	>5000 mg/kg	Rat
Petroleum distillates, hydrotreated light	LD50 dermal	>2000 mg/kg	Rabbit
Petroleum distillates, hydrotreated light	LD50 inhalation	>5.2 mg/l/4hr	Rat
Dimethyl succinate	LD50 oral	6,892 mg/kg	female rat
Dimethyl succinate	LD50 inhalation	>2,000 mg/kg	Rat
Dimethyl succinate	LD50 dermal	>5000 mg/kg	Rabbit
Diethylene Glycol Butyl Ether	LD50 oral	2,410 mg/kg	Mouse
Diethylene Glycol Butyl Ether	LD50 dermal	2,764 mg/kg	Rabbit
Dipropylene Glycol Methyl Ether Acetate	LD50 oral	>5000 mg/kg	
Dipropylene Glycol Methyl Ether Acetate	LD50 dermal	>2000 mg/kg	
Dipropylene Glycol Methyl Ether Acetate	LC50 vapor	>20 mg/l	
Dibasic ester	LC50 vapor	35 mg/l	Rat
Dibasic ester	LD50 dermal	>2250 mg/kg	Rabbit
Dibasic ester	LD50 oral	>5000 mg/kg	Rat
Polyoxyethylenealkylether	LD50 oral	2600 mg/kg	Rat
Polyoxyethylenealkylether	LD50 dermal	2000 mg/kg	Rat

### IRRITATION/CORROSION

Combination of dibasic acids, solvents, and surfactants are corrosive to the eye and irritating to the skin on prolonged contact.

### SENSITIZATION

No known sensitizers in this product.

### MUTAGENICITY

No mutagenic components identified in this product.

### CARCINOGENICITY

No known carcinogenic components identified in this product.

# SAFETY DATA SHEET

## REPRODUCTIVE TOXICITY

No known reproductive components identified in this product.

## TERATOGENICITY

No known teratogenic components identified in this product.

## STOT - SINGLE EXPOSURE

Product components are GHS category 3 central nervous system suppressors on acute high exposure

## STOT - REPEATED EXPOSURE

Repeated exposure is likely to impact the CNS system and liver but not rated under GHS.

## ASPIRATION HAZARD

This product is an aspiration hazard and could cause chemical pneumonitis if aspirated into the lungs.

## POTENTIAL ACUTE HEALTH EFFECTS

Eye contact	Severe irritation and permanent damage if left in the eye
Inhalation	Central nervous system effects with dizziness and drowsiness
Skin Contact	Defats the skin and causes irritation
Ingestion	Aspiration hazard

## SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

Eye contact	May cause irreversible damage if left in the eyes.
Inhalation	Symptoms are expected to be short term unless the product is misused.
Skin contact	May cause dermatitis
Ingestion	Aspiration into the lung can cause chemical pneumonitis; no specific hazards with ingestion.

## DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURES

### Short term exposure

Potential immediate effects	Eye irritation; skin irritation
Potential delayed effects	Eye damage; Skin damage

### Long term exposure

Potential immediate effects	Skin irritation; defatting
Potential delayed effects	CNS depression

## POTENTIAL CHRONIC HEALTH EFFECTS

General	Eye damage; skin damage; CNS depression with liver and kidney function impact.
---------	--

## NUMERICAL MEASURES OF TOXICITY

Acute toxicity estimates	<u>acute toxicity point estimate (ATE)</u>
Route	
Oral	5000
Dermal	2500
Inhalation	12

---

## 12. ECOLOGICAL INFORMATION

### TOXICITY

<u>Species</u>	<u>Test Information</u>	<u>Concentration</u>	<u>Component</u>
Fish	NOEC/NOEL (modeled)	>0.01-<0.1 mg/l	Distillates(petroleum) hydrotreated light
Aquatic crustacea	NOEC/NOEL (modeled)	>0.1 - <0.1 mg/l	Distillates(petroleum) hydrotreated light
Microorganisms	LL/EL/IL50	>100 mg/l	Distillates(petroleum) hydrotreated light
Fish	LC50 - 48 hr	3.3 - 8.8 mg/l	Polyoxyethylenealkyl ether
Aquatic crustacea	LC50 - 48 hr	>1 mg/l	Polyoxyethylenealkyl ether
Bluegill sunfish	LC50 static 96 hr	1,300 mg/l	Diethylene glycol butyl ether
Daphnia magna	EC50 static 48 hr	>100 mg/l	Diethylene glycol butyl ether



# SAFETY DATA SHEET

Green Algae	ErC50 static - 96 hr	>100 mg/l	Diethylene glycol butyl ether
Bacteria	EC10 -act. Sludge 30 min	>1995 mg/l	Diethylene glycol butyl ether

## PERSISTENCE AND DEGRADABILITY

Components are readily biodegradable and products of biodegradation are less toxic than the chemicals, themselves. The solvent components are expected to evaporate into the air. The acutely toxic polyoxyethylenealkyl ether (surfactant) is acutely toxic but biodegradable.

## BIOACCUMULATIVE POTENTIAL

Not expected to bioaccumulate.

## MOBILITY IN SOIL

Soil/water partition coefficient ( $K_{oc}$ )

No data available

Mobility

No data available

## OTHER ADVERSE EFFECTS

Surfactants are toxic to aquatic organisms.

---

## 13. DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Generating waste is to be avoided and/or minimized whenever possible. Disposal of this product, solutions and any by-products should comply with the local regulatory requirements. Waste from use of this product is likely to be able to be disposed of through the sewer system but verify this with local authorities prior to adopting this method of disposal. Unused, excess material beyond its manufacturer shelf life should be disposed of in accordance with local regulatory requirements. The product is combustible and should be treated for disposal as a liquid combustible.

# SAFETY DATA SHEET

## 14. TRANSPORT INFORMATION

Consolidated Transportation of Dangerous Goods Regulations including Amendment SOR/2019-101

TDG Classification	RB Screen Wash
UN Number	NA
Shipping Name and Description	Canadian TDG Classification: Not regulated as a dangerous good when packages in a small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.
Transport Hazard Class	NA
Packing Group Category	NA
Special Provisions	NA
Explosive Limit and Limited Quantity Index	NA
Excepted Quantities	NA
ERAP Index	NA
Passenger Carrying Vessel Index	NA
Passenger Carrying Road Vehicle or Passenger Carrying	NA

### INTERNATIONAL AIR TRADE ASSOCIATION (IATA)

IATA 58th Edition Information	RB Screen Wash
UN Number	NA
Proper Shipping Name Description	NA
Class or Division	NA
Hazard Label(s)	NA
Packing Group	NA
EQ - 2.6 Dangerous Goods in Excepted Quantities	NA
Passenger Aircraft - Limited Quantity Packing Instructions	NA
Passenger Aircraft - Limited Quantity Max net Qty/Pkg	NA
Passenger Aircraft - Packing Instructions	NA
Passenger Aircraft - Quantity Max Net Qty/Pkging	NA
Cargo Aircraft only - Packing Instructions	NA
Cargo Aircraft only - Max Net Qty/Pkging	NA
Special Provisions 4.4	NA
ERG Code	NA

### INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG CODE)

IMDG 2016 EDITION	RB Screen Wash
UN Number	NA
Proper Shipping Name Description	NA
Class or Division	NA
Subsidiary Risks	NA
Packing Group	NA
Special Provisions	NA
Limited Quantities	NA
Excepted Quantities	NA
Packing Instructions	NA
Packing Provisions	NA

# SAFETY DATA SHEET

IBC Instructions 4.1.4	NA
IBC Provisions 4.1.4	NA
Portable tanks and bulk containers - tank instructions	NA
Portable tanks and bulk containers - provisions	NA
EmS	NA
Stowage and Handling	NA
Segregation	NA
Properties and observations	NA

**SPECIAL PRECAUTIONS FOR USER**

**Transport within user's premises:** always transport in containers that are upright and secure.  
 Ensure that persons transporting the product are trained in spill or accident prevention.

## 15. REGULATORY INFORMATION

**CANADIAN LISTS**

Canadian NPRI  
CEPA Toxic Substances  
Canada Inventory

**The following components are listed:** Distillates, petroleum hydrotreated light  
**The following components are listed:** None  
 All components are listed or exempted.

## 16. OTHER INFORMATION

**CREATION/REVISION SUMMARY:**

Created on: February 20, 2020  
 to be compliant with Canadian WHMIS requirements.

**AUTHORED BY:**

Cheryl Sykora, CIH, CSP, CHMM  
 Registered Specialist, SDS and Label Authoring #118534  
 LEGEND TECHNICAL SERVICES, INC.  
 88 Empire Drive, Saint Paul, Minnesota 55103  
 651-221-4085



THE INFORMATION RELATES TO THIS SPECIFIC INFORMATION. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.