

LS-350™



Long Sleeve Folding Attachment

FEATURES

- Pre-folds long sleeves before the garment enters the folding machine
- Works with most types of long-sleeve garments
- Improves product appearance and increases productivity

The Amscomatic LS-350 expands the capabilities of the K-950 Automatic Folding System to include the automatic folding of long-sleeve garments. The LS-350's modular design allows for simple installation, including repositioning the K-950's touch-screen control panel to the top of the LS-350. Since the K-950's touch-screen also includes LS-350 folding parameters, complete control of all settings is at the operator's fingertips. In addition, folding parameters from the LS-350 are automatically incorporated with those of the K-950 for each Job Recall™ setting (Job Recall™ provides storage and retrieval of up to 99 fold settings for quick changeover). This merging of folding parameters significantly enhances operating efficiency.

The LS-350 quickly and efficiently folds most kinds of long-sleeve garments. It has no effect on normal short-sleeve garment folding, so there's no need to change the configuration of the folding line when changing garment type. It also incorporates Amscomatic's patented dual-belt (upper and lower) transport system for maximum versatility and excellent performance when folding garments printed with high density or gel inks. The LS-350's solid top belt can be replaced with an optional Split Belt. The Split Belt option consists of



Shown with optional Split Belt feature

dual top belts with a gap that allows buttons, plackets, and zippers to pass through cleanly and smoothly.

The LS-350 is built to specifications established by the European Committee for Standardization® (CE) and Underwriters Laboratories® (UL), and it's backed by a one-year limited warranty. Amscomatic folders are engineered for dependable performance and low maintenance in demanding, high-production environments, and can be easily integrated with other Amscomatic equipment into automatic folding/bagging/sealing systems.

SPECIFICATIONS

	LS-350
Electrical Requirements ¹	110 V, 1 ph, 3 A, 50/60 Hz, 0.4 kW 208/230 V, 1 ph, 1.5 A, 50/60 Hz, 0.4 kW
Overall Size (L x W x H)	126 x 81 x 130 cm (49.5" x 32" x 51")
Shipping Weight	330 kg (725 lb)

¹If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available. Contact The M&R Companies for details



The M&R Companies
M&R • NUARC • AMSCOMATIC

M&R Sales and Service, Inc. 1N372 Main Street, Glen Ellyn, Illinois 60137-3576 USA

USA: 800-736-6431 / 630-858-6101 / Fax: 630-858-6134 • Outside USA: +1-847-967-4461 / Fax: +1-847-967-0417

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2013 M&R Printing Equipment, Inc. All rights reserved. 011613