

Mimaki genuine warming laminator LA-140W/160W



- Max. Speed 7,500mm/min. *1
- Safety design for operator protection
- Warming function prevents Silvering^{*2} of UV print

New standard model with comfortability and user-friendliness

1 Reduce Silvering to retain the beauty of original print

Equipped with warming function available to heat up to max. 60 degrees.
Laminating with heating improves the adhesion of lamination to reduce Silvering caused by unevenness of print surface due to property of ink.

2 Operation speed equivalent with high class models

Max. laminating speed is 7,500mm/min. (*1)
Operation speed equivalent with high class models is achieved. The introduction of [LA-160W] with [UCJV300/150-160] saving ink drying time due to instant ink curing can duly support your job focusing quick delivery.

3 Excellent operability even by one operator as simple and safe

Laminating speed is max. 7,500mm/min. (*1), steplessly adjustable by dial. The temperature of warming is adjustable up to 60 degrees and settable every one degree from operation panel. Laminating pressure adjustment is also easy by machine handle. Taking-up function of laminated media enables one-man operation.

4 Safety design for operator protection

Safety functions are provided : an emergency stop and a protection function by laser.
They are for secured working environment to protect operators from rolling-in accident.

■ Specificaiton

Item	LA-140W	LA-160W
Laminating width	Max.1,400mm(55.1in)	Max.1,580mm(62.2in)
Laminating speed	Max. 7,500mm /min	
Film Thickness	Max. 35mm	
Core diameter	3inch	
Warm temperature	Max. 60 degrees	

Item	LA-140W	LA-160W
Power consumption	1800W or less	
Attached shaft (with measure scale)	3inch× 5 pcs.	
Outer dimensions (WxDxH)	1,830×550×1,280mm 72.0×21.7×50.4in	2,000×550×1,280mm 78.8×21.7×50.4in
Weight	185kg(407.9lb)	205kg(451.9lb)

* Specifications, designs and dimensions stated in this list may be subject to change without notice due to technical improvement etc.

*1 Max speed is 6,000mm/min. in area of power supply 50Hz.

*2 Silvering: Whitening phenomenon of graphic by engulfing air babbles on laminating.

Mimaki™ MIMAKI ENGINEERING CO., LTD.
mimaki.com
2182-3 Shigeno-otsu, Tomi-city, Nagano 389-0512, Japan
Tel: +81-268-64-2281

Mimaki Global Network

USA	MIMAKI USA, INC.	Europe	MIMAKI EUROPE B.V.
Brazil	MIMAKI BRASIL COMERCIO E IMPORTACAO LTDA	Indonesia	PT. MIMAKI INDONESIA
India	MIMAKI INDIA PRIVATE LIMITED	Australia	MIMAKI AUSTRALIA PTY. LTD.
Taiwan	MIMAKI ENGINEERING (TAIWAN) CO.,LTD.	China	SHANGHAI MIMAKI TRADING CO.,LTD.
Singapore	MIMAKI SINGAPORE PTE. LTD.	Thailand	MIMAKI (THAILAND) CO.,LTD.