



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

**Sales, Service & Distribution Center**  
Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

**Manufacturing, Sales, Service & Distribution Center**  
Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

**Sales and Tech Service Support**  
Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE NON-DETERGENT MOTOR OILS

## DESCRIPTION

LUBRIPLATE Non-Detergent Motor Oils are manufactured from premium quality base-stocks, for use where detergent oils are not required or desired.

## ADVANTAGES

- ⇒ High Viscosity Index
- ⇒ High Flash and Fire Points
- ⇒ Extra Clean Motor Oils

## APPLICATIONS

Recommended wherever operating conditions require an oil of this type:

- ⇒ API SA
- ⇒ Certain Internal Combustion Engines
- ⇒ Transmissions
- ⇒ Gear Cases
- ⇒ AGMA Non-E. P. Gear Oils



## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS				
		10W	20W-20	30	40	50
<b>Viscosity:</b>						
SUS @ 210°F	D-2161	47	56	67	76	103
SUS @ 100°F	D-2161	180	310	505	731	1,300
cSt @ 100°C	D-445	6	9	12	14	21
cSt @ 40°C	D-445	34	60	97	135	245
Viscosity Index	D-2270	122	117	109	98	97
API Gravity	D-287	31.5	30.7	30.1	29.5	27.3
Flash Point, °F/°C	D-92	425/219	450/232	485/252	525/274	535/280
Pour Point, °F/°C	D-5950	-35/-37	-25/-32	-5/-21	0/-18	0/-18
Color	D-1500	1½-	2-	2½-	3	7-
AGMA Number		1	2	3	4	5

### PACKAGING AVAILABLE

	<b>10W</b>	<b>20W-20</b>	<b>30</b>
Carton, 12/1 Quart Plastic Bottles	L0804-054	L0806-054	L0807-054
5 Gallon Pail	L0804-060	L0806-060	L0807-060
55 Gallon Drum	L0804-062	L0806-062	L0807-062

### PACKAGING AVAILABLE

	<b>40</b>	<b>50</b>
Carton, 12/1 Quart Plastic Bottles	L0808-054	L0809-054
5 Gallon Pail	L0808-060	L0809-060
55 Gallon Drum	L0808-062	L0809-062