TINA2 3D Printer Printing by Poloprint APP

1.Go to the menu bar and click : Control Interface - Network Settings

Infor screen Prepare	
Control	
Print from SD	

Control Show ip Wifi Device Info Connect to wifi Wifi OTA Update

Main Temperature Z offset Setting Wifi network Language

Connect to wifi Open the App Goto wifi setting Input wifi password 5G wifi not support 2.Get into poloprint APP, choose 'device's wifi setting'



It will show the IP address in the APP

15:52			
	Add Printer		
	Printer Name(Option	ia()	
	192.168.0.247		
	TINAO		
,	Machine Type	*	
		ADD PRINTER	
	<	0	=

You can also see the IP address on the screen of the printer

0°C ◯ 55°C	TINA II 3D PRINTER		\$
X 100	Y 90	Ζ	100
F _{R 100%}	· · · ·		
192.168.0.247			

3. Printing via APP

The APP main interface displays the cloud model file for the user to select the model to be printed. After selecting the model to be printed, click the model icon, the print button will appear in the lower right corner, and you can download and upload the model for printing.



Print the Gcode-file in TF card via the app



4. Printer control and Management

Poloprint can control and manage your printers.



15:31			a 🕿 🕮
	Printers		
((-	TINA2 192.168.0.247 TINA2 D0D00000		۵
(ŀ	192.168.0.6 192.168.0.6 F152S D00000000		۵
(1-	192.168.0.42 192.168.0.42 TINA2 D0000000		\$
((•	192.168.0.248 192.168.0.248 NINA 11122233		۵
0			•
	<	0	=