



- TERRACOTTA
- QUARRY TILES
- PORCELAIN TILES TEXTURED
- RUSTIC SINGLE-FIRED TILES
- UNPOLISHED STONE AND AGGLOMERATES



### WHAT IT'S FOR

- Protects natural and textured porcelain stoneware, textured single-fired ceramic tiles, terracotta and rough-finished natural stone against dirt deposits and wear due to normal use.
- Creates a protective film.
- Ideal as a finishing coat for protecting terracotta, natural stone and unpolished agglomerates.

### ADVANTAGES

- Ideal for textured porcelain stoneware floors in high traffic areas.
- Has excellent adhesive powers on rough-finish porcelain surfaces.
- High gloss effect without polishing.
- Protects against dirt deposits and wear due to normal use.

### HOW TO USE IT

**No dilution required: ready to use.**

**Application:**

- **To protect textured porcelain tiles:** apply undiluted with a cloth and wait until completely dry. If necessary, apply a second coat at right-angles to the first. Wait until completely dry before walking on the floor. No need to polish.
- **To finish terracotta and stone:** on surfaces treated beforehand with FILAFOB or FILAW68 apply undiluted with a fleece pad or cloth and wait until completely dry. No need to polish. You can complete the treatment with a finishing wax (FILAMATT, FILASATIN, FILACCLASSIC, FILALONGLIFE).
- **For maintenance:** diluted solution of FILACLEANER

#### COVERAGE

With one litre:

Terracotta/Stone	30 m <sup>2</sup>
porcelain tiles	30/40 m <sup>2</sup>

"Coverage shown is for guidance purposes only and refers to single coats"

#### Packaging

1 litre cans in boxes of 12.  
5-litre cans in boxes of 4.

#### WARNINGS

- Do not disperse into the environment after use.
- Do not disperse into the environment after use.
- In some cases FILAJET may have problems with adhesion, so we recommend testing the product's adhesive capacity on the floor beforehand.

#### TEMPERATURES

**Storage temperature:** from 5° to 30° C  
The product must be applied to material with a temperature between 10° and 30°C.

#### COMPOSITION

Aqueous emulsion of acrylic polymers, polyethylene waxes, wetting resins, plasticisers and additives (preservative and anti-foam agent).

#### LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.

Pursuant to It.Leg.Dec. No.161/06:

**Category:** high performance one component paints (floor coatings).  
EU limit value for this product (Cat: 1/1): 140 g/l (2010). This product contains no more than 37.95 g/l

#### TECHNICAL FEATURES

**Appearance:** liquid  
**Colour:** milky white  
**Odour:** typical acrylic  
**Density:** 1.023 kg/l  
**pH:** 8.0

*This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.*