

MADE IN THE USA

HARLEY DAVIDSON XG STREET 500/750 DIY Seat Re-Cover kit




Basic Tools Required

- -Staple Gun
- -Screwdriver
- -Pliers

*air powered upholstery stapler recommended



we recommend taking pictures along the way to keep track of which way things went on.



- -Push 2 round tabs down with screwdriver
- -Pull mounting bracket out





- Insert small screwdriver under stock cover to lift stock staples
- -Pull staples out with pliers
- -Remove stock seat cover
- -Install new TUFFSIDE seat cover





- -fold seam over 1 edge of the seat pan
- -seam should run along the edge of the seat pan






Pull front corners over and install 2 staples in order below

Ensure cover is pulled tight and corners are lined up before stapling.

Pull rear corners over and install 4 staples in order below

Ensure cover is pulled tight and corners are lined up before stapling.



Pull center side edges over and install staples in order below

Ensure cover is pulled tight and corners are lined up before stapling.





Flip seat over to ensure things are straight before adding more staples.

Then work your way around with more staples ensuring the edge stays lined up with the stock seat pan. Check your work before adding to many staples.

We recommend stapling one side at a time.

The second side will require some effort to pull the cover tight and remove any wrinkles.







-finish the front staples last

Slide rear mount back in when finished

- -Covers are vinyl and are water resistant not water proof.
- -Proper care and maintenance is the customers responsibility.
- -Most vinyl/upholstery cleaners work well
- -Some stitch colors may fade if stored in direct sunlight for extended periods of time motorcycle covers are recommended if storing bike outside.
- -Covers are not guaranteed against tearing or fading
- -Covers can be installed by customers but an experienced upholstery installation shop is always recommended
- -Covers are designed to be pulled tight and fit snug and wrinkle free, however excessive force on stitches can cause failure of seams please use caution when pulling cover edges
- -If using pneumatic staple us correct pressure to avoid tearing through the material