

Specifications



SHC1000W



Peephole
Φ 12mm



Peephole
Φ 14mm

Smart Peephole DoorCam

Model	SHC1000W 12	SHC1000W 14
Peephole Barrel	15/32" (12 mm)	5/9" (14 mm)
Applicable Door Thickness	1-1/8" to 2-1/4" (28-58 mm)	1-3/4" to 3-1/8" (43-80 mm)
View Angle	90°	
Peephole Type	Optical grade lens peephole	
LCD Screen	2.7" TFT	
Storage	micro SD card (included)	
Wireless	Wi-Fi (802.11 b/g)	
File Format	JPEG	
Power Source	4* AA batteries (included)	
Operating Temperature	32 °F ~113 °F (0 °C ~45 °C)	
Size (WxHxD)	3.4"x6.2"x1.3" (87 x 158 x 34 mm)	
Weight	6 oz(170 g) (without batteries)	
Built-in Sensor	Knocking sensor	
Contents	Peephole,Base flange, Tightening tool,microSD card, 4 AA batteries, User manual. Quick start guide	



MAS200

Motion Detector

Model	MAS200
Detection Angle	90°(horizontal)
Detection Distance	Centerline: 13 ft (4 m) Side: 5 ft (1.5 m)
Transmission Distance to Receiver	32 ft (10 m)
Power Source	1 CR2450 battery (included)
Splash-proof	IPX4
Operating Temperature	32 °F ~113 °F (0 °C ~45 °C)
Compatible Model	SHC1000, SHC1000W
Size (WxHxD)	Door knocker casing: 2.4" x 4" x 1.1" (60 x 100 x 28 mm) Motion sensor unit: 1.7" x 2" x 0.5" (44 x 52 x 14 mm) Receiver unit: 1.5" x 1.1" x 0.2" (37 x 29 x 6 mm)
Weight	Door knocker casing:1.3 oz(36 g) Motion sensor unit:0.7 oz(21 g) (without batteries) Receiver unit:0.2 oz(5.5 g)
Package Contents	Door knocker casing; Motion sensor unit (inside knocker casing); Receiver unit; Magnetic wall mount; Battery lock; Screwdriver; 1 CR2450 battery.